



- 注)
NOTES:
1. 材質
MATERIAL
銅合金 (板厚: 0.3)
COPPER ALLOY (THICKNESS : 0.3)
 2. メッキ仕様
TERMINAL PLATING
接点部 : 金メッキ 0.25 μm MIN.
CONTACT AREA : GOLD 0.25 MICROMETER MIN.
圧着部 : 錫メッキ 1.0 μm MIN.
CRIMP AREA : TIN 1.0 MICROMETER MIN.
下地メッキ : ニッケルメッキ 2.0 μm MIN.
UNDER PLATE : NICKEL 2.0 MICROMETER MIN.
 3. 適用電線範囲 : UL 2517 , AWG #16
APPLICABLE WIRE RANGE : UL2517 , AWG #16
 4. 被覆外径 : φ2.2~φ2.7
INSULATION EXTERNAL DIA : φ2.2~φ2.7
 5. 適用ハウジングアッセンブリ : 51195 シリーズ
APPLICABLE HOUSING ASS'Y : 51195 SERIES
 6. 本製品は59319-**-90の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 59319-**-90.

バラ状 LOOSE	59319-0128	59319-**-28
連鎖状 CHAIN	59319-0028	
端子形状 TERMINAL CONFIGURATION	MATERIAL No.	MODEL NO.

DO NOT SCALE DRAWING

EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:	EC NO. DRWN: CHK: APPR:

RELEASED
EC NO. J2004-3411
DRWN: Y.WADA '04/03/29
CHK: M.SASAO '04/03/29
APPR: M.SASAO '04/03/29

MATERIAL 材料	#
FINISH 仕上げ	#
WIRE RANGE 適用電線範囲	#
INS. RANGE 被覆外径	#

GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差	10 UNDER 未満	±0.2
	10 OVER 30 UNDER 以上 未満	±0.25
	30 OVER 以上	±0.3
ANGLE 角度		±3°

SCALE 1:1	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH
DRAWN BY & DATE Y.WADA '04/03/29	CHECKED BY & DATE M.SASAO '04/03/29
APPROVED BY & DATE M.SASAO '04/03/29	CAD FILENAME SD-59319-002.S01

DIMENSIONS: <input type="checkbox"/> mm <input type="checkbox"/> INCH <input checked="" type="checkbox"/> mm ONLY		SHT REVISE ON CAD ONLY
THIRD ANGLE PROJECTION		
TITLE: POWER CONN. REC. CRIMP TERMINAL -LEAD FREE-		
MOLEX MOLEX INCORPORATED		
MATERIAL NO. SEE CHART	DRAWING NO. SD-59319-002	SHEET NO. 1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		SIZE B