

Datasheet for 76650-0229

General Information

Kit Part Number:	76650-0229
Connector Type:	Wire-to-Wire
Solution:	Free Hanging Connectors
Molex Family:	2.00 mm, Micro-Fit 3.0™, PicoBlade™
Certificates:	N/A
Country of Origin:	Kit assembled in U.S.A

Specifications

Circuit Size:	2, 3, 4
Current Rating:	0.8-1, 1-2A, 5A
Mounting Style:	Free-Hanging
Orientation:	Plugs, Receptacles
Pitch:	1.25mm (.049"), 2.00mm (.079"), 3.00mm (.118")
Tool Included:	No
Voltage Rating:	125V, 250V
Wire Gauge (AWG):	(24-20), 28-24, 32-28

Product Highlights

1.25mm (.049") pitch PicoBlade™ system is designed for high-density harness applications. PicoBlade™ provides the same 1.0 amperes of current as similar 2.00mm (.079") pitch systems, but in a more compact design. PicoBlade™ is offered in wire-to-board and wire-to-wire options. The system saves about 45% of PCB space compared to typical 2.00mm wire-to-board systems. The Micro-Fit 3.0™ is a unique interconnect system designed to meet the need for a high contact density signal or power connector and incorporates many of the features previously found on larger power connectors. These 3.00mm (.118") pitch connectors are the perfect choice when you need compact connectors that carry up to 5 amperes of current. This family has a very thin housing design, with the housings having a 2.7mm maximum thickness. The 51005 series (9.2mm) mated with the 51006 series (10.8mm) has a mated length of 14.8mm. The plug and receptacle mate with an audio click, and remain mated very strongly with locking tangs on both sides.

Features and Benefits

- Polarization prevents mismatching
- Locking tang for secure housing retention
- Two solder tabs for better connection to the PCB
- Integral pull tabs for ease in unmating
- Very thin housing design, 2.7mm (.106")
- Box-type spring contact for high normal force
- 4 points of contact for optimum reliability

Applications

- Handheld Devices
- Computers and Workstations
- Car Radios
- Process controls
- Fitness equipment

<http://www.molexkits.com>

- Medical monitoring, Lab equipment
- Gaming and Vending
- Set top boxes
- Alarm systems
- Patient monitors
- Office Equipment
- Power Supplies
- Fan Tray Assemblies
- DVD players
- Cash dispensers

Bill of Materials

Molex Part No.	Description	Quantity
51021-0400	1.25mm (.049") Pitch PicoBlade™ Receptacle, 4 Circuits	5
51021-0300	1.25mm (.049") Pitch PicoBlade™ Receptacle, 3 Circuits	5
51005-0300	2.00mm (.079") Pitch Wire-to-Wire Receptacle Housing, 3 Circuits	5
51005-0200	2.00mm (.079") Pitch Wire-to-Wire Receptacle Housing, 2 Circuits	5
51021-0200	1.25mm (.049") Pitch PicoBlade™ Receptacle, 2 Circuits	5
51047-0400	1.25mm (.049") Pitch PicoBlade™ Plug, 4 Circuits	5
51047-0300	1.25mm (.049") Pitch PicoBlade™ Plug, 3 Circuits	5
50013-8100	Female Crimp Terminal, Loose, for 2.00mm (.079") Pitch, 51005 Receptacle	50
50012-8100	Male Crimp Terminal, Loose, for 2.00mm (.079") Pitch, 51006 Plug	50
50058-8000	PicoBlade™ Crimp Terminal, Female, 32-28 AWG	50
50133-8100	PicoBlade™ Crimp Terminal, Male, 32-28 AWG	50
51047-0200	1.25mm (.049") Pitch PicoBlade™ Plug, 2 Circuits	5
51005-0400	2.00mm (.079") Pitch Wire-to-Wire Receptacle Housing, 4 Circuits	5
51006-0200	2.00mm (.079") Pitch Wire-to-Wire Plug Housing, 2 Circuits	5
51006-0300	2.00mm (.079") Pitch Wire-to-Wire Plug Housing, 3 Circuits	5
51006-0400	2.00mm (.079") Pitch Wire-to-Wire Plug Housing, 4 Circuits	5
43030-0007	Micro-Fit 3.0™ Crimp Terminal, Female, 24-20 AWG	50
43031-0007	Micro-Fit 3.0™ Crimp Terminal, Male, 24-20 AWG	50
43645-0200	3.0mm (.118") Pitch Micro-Fit 3.0™ Receptacle, 2 Circuits	5
43645-0300	3.0mm (.118") Pitch Micro-Fit 3.0™ Receptacle, 3 Circuits	5
43645-0400	3.0mm (.118") Pitch Micro-Fit 3.0™ Receptacle, 4 Circuits	5
43640-0201	3.0mm (.118") Pitch Micro-Fit 3.0™ Plug, 2 Circuits	5
43640-0401	3.0mm (.118") Pitch Micro-Fit 3.0™ Plug, 4 Circuits	5
43640-0301	3.0mm (.118") Pitch Micro-Fit 3.0™ Plug, 3 Circuits	5

Recommended Molex Tool

Molex Part No.	Description
63811-7800 (not included in kit)	Click for more info
57046-5000 (not included in kit)	Click for more info