

## This document was generated on 02/26/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0877051021			4	
Status:	Active 1.00mm Pitch DDR-II DIMM Socket, Vertical, Center Keys, 3.18mm Tail Length, Beige Latches, 0.38µm Gold (Au) Plating, with Beveled Metal Pins, 240 Circuits, Lead-Free		5	
Description:				
Documents:			ALL DE LE COLOR DE	
<u>3D Model</u>		Product Specification PS-87705-002-001 (PDF)	1 <b>0</b>	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)		
Agency Certification				• - Reference only
CSA		LR19980	Series inage	- Reference only
UL		E29179		
General			EU ELV	
Product Family		Mamary Madula Saakata	Not Relevant	
Series		Memory Module Sockets		Ohine DellO
		<u>87705</u>	EU RoHS	China RoHS
Component Type		Socket	Compliant	
Electrical Model		Yes	REACH SVHC	
JEDEC Outline		MO-237	Not Contained Per	
Product Name		DDR2 DIMM	-ED/88/2018 (15	
UPC		756054857298	January 2019)	
Discolored			Halogen-Free	
Physical		<b></b>	<u>Status</u>	
Circuits (Loaded)	,	240	Not Low-Halogen	
Durability (mating cycles max)		25		n, please visit <u>Contact U</u>
Entry Angle		Vertical (Top Entry)		, <b>-</b>
Flammability		94V-0	China ROHS	Green Image
Housing Color		Black	ELV	Not Relevant
Keying to Mating Part		Yes	RoHS Phthalates	Not Contained
Latch Color		Beige	1	
Material - Metal		Brass, Phosphor Bronze		
Material - Plating Mating		Gold		
Material - Plating Termination		Tin	Search Parts in th	his Series
Material - Resin		High Temperature Thermoplastic	87705 Series	
Net Weight		9.965/g		
PC Tail Length		3.18mm	Mates With	
PCB Retention		Yes	JEDEC Standard	1.27mm Modules
PCB Thickness - Reco	ommended	2.40mm	j L	
Packaging Type		Tray		
Pitch - Mating Interface	9	1.00mm		
Plating min - Mating		0.381µm		
Plating min - Termination		2.540µm		
Temperature Range - Operating		-10° to +85°C		
Termination Interface: Style		Through Hole		
Electrical		0.54		
Current - Maximum per Contact		0.5A		
Voltage - Maximum		30V		
Voltage Key		1.8V, Center		
Solder Process Data				
	ess Temperature (seconds)	005		
Lead-freeProcess Cap		SMC&WAVE		
Max. Cycles at Max. Process Temperature		001		
Process Temperature	max. C	260		
Material Info				

**Reference - Drawing Numbers** Electrical Model Document Product Specification S-Parameter Model Sales Drawing

EE-87705-001 PS-87705-002-001 SP-87705-001 SD-87705-001

## This document was generated on 02/26/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION