# 96W Intelligent Series - MU096I200AQI22 (DALI,1ch)

#### Features

- · Compliant with Class 2 Power supply safety standards
- Constant current LED driver
- Support DALI type 6
- 1 LED channel, output current can be changed from 200mA to 2000mA
- Mode of wiring: At the bottom of wiring.
- Constant power maximum is 96W
- Normal life time is 50000 hours ( at the case's temperature of 70 $^\circ\!\!\!{\rm C}$  )
- Dimming range 0.1%~100%
- Protection compliant with IP20
- 5-year warranty



178.8 × 83.4 × 31.6 mm

### Electrical Specifications

Input Voltage range	100~277 VAC
Frequency range	47~63 Hz
Input current	1.2A MAX at 100VAC
Rated power	96W
Power factor	>0.9 at 230V,50Hz,full load
Efficiency	85%(typical) at 230V,50Hz,full load
Output volatge range	36~48VDC
Output current range	200~2000mA
Protections	Thermal Protection, Short-circuit Protection, No-load Protection, Over-Power Protection


### Environmental Specifications


Operating temperature	-25 ~+50℃
Storage temperature	-40 ~+85℃
Cooling method	Convection
Maximum case temperature	85℃
Life Time	50000 hours ( at the case's temperature of 70 $^\circ\!\!\!\!\!^\circ$ )
Reference dimension	178.8×83.4×31.6 (mm) (LxWxH)

### Safety & EMC Compliance

CUL	UL8750,UL1310
Withstand Voltage	I/P-O/P : 3.75KVAC , I/P-FG : 1.875KVAC, O/P-FG :0.5KVAC
CE	EN61347-1,EN61347-2-13
Conducted emissions	EN55015,FCC Part 15 ClassB
Radiated emissions	EN55015,FCC Part 15 ClassB
Harmonic current emission	IEC62386-101/102/207
Electromagnetic immunity	EN61000-3-3;EN61000-4-2,3,4,5,6,8,11;EN61547

## Mechanical Specification (mm)







Schematic Diagram

