Note: This datasheet may be out of date.
Please download the latest datasheet of PTGL13AR3R7H4B71B0 from the official website of Murata.

Manufacturing Co., Ltd.

https://www.murata.com/en-us/products/productdetail?partno=PTGL13AR3R7H4B71B0

### PTGL13AR3R7H4B71B0











### Appearance & Shape







(in mm)



### **Features**

- 1. Best suited to meet the requirements for power supplies and motor protection. Error-free operations are assured by rush current.
- 2. Circuit is protected until current is turned off.
- 3. Restores the original low resistance value automatically once the overload is removed.
- 4. Non-contact design leads to long life and no noise.

  Durable and strong against mechanical vibration and shock because it is a solid element.



Limited Usage	Consumer Grade
Other Usage	Transformers     Transistors     Fluorescent Lamps



# Packaging Information

Packaging	Specifications	Minimum Order Quantity
В0	Bulk(Bag)	300

1 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2020/01/24



Note: This datasheet may be out of date.  $\underline{ \text{Please download the latest datasheet of PTGL13AR3R7H4B71B0 from the official website of Murata} \\$ 

7.5mm

0.6mm

Lead

1.25g

F: Lead Space

d: Lead Diameter

Shape

Mass

Manufacturing Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=PTGL13AR3R7H4B71B0

# PTGL13AR3R7H4B71B0



Max. Voltage	80V
Hold Current(25°C)	405mA
Measure Condition of Hold Current	(at +25°C)
Hold Current (2)	310mA
Measure Condition of Hold Current (2)	(at +60°C)
Trip Current	750mA
Measure Condition of Trip Current	(at +25°C)
Trip Current(2)	860mA
Measure Condition of Trip Current(2)	(at -10°C)
Max. Current	5.5A
Resistance (25°C)	3.7Ω
Resistance Value Tolerance (at 25°C)	±25%
Curie Point(typ.)	120°C
Power Consumption(typ)	2.3W
Operating Temperature Range	-10°C to 60°C
D: Outer Dimension	13.5mm
Thickness	4.5mm

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





URL: https://www.murata.com/

Last updated :2020/01/24


# PTGL13AR3R7H4B71B0







Resistance-Temperature Charac.



Protective Threshold Current Range

Operating Time (Typical Curve)

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated :2020/01/24