Note: This datasheet may be out of date.

Please download the latest datasheet of DLW43SH101XP2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=DLW43SH101XP2%23

"#" indicates a package specification code.











< List of part numbers with package codes >

DLW43SH101XP2K


DLW43SH101XP2L

DLW43SH101XP2B



Appearance & Shape









Applications

Powertrain/Safety Automotive Usage



Packaging Information

Packaging	Specifications	Standard Packing Quantity
K	330mm Embossed Tape	2500
L	180mm Embossed Tape	500
В	Bulk(Bag)	100



Features

- 1. Small size: L4.5xW3.2xT2.7mm (EIAcode: 1812) Tolerance: +/-0.2mm
- 2. It realized common mode inductance of 100microH (at 0.1MHz) though it is small size.
- 3. Suitable for noise suppression from low frequency range (0.1MHz).

Applications

For Automotive.

Common mode noise suppression of automotive LAN for Flex Ray etc.

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



DLW43SH101XP2#

Note: This datasheet may be out of date.

Please download the latest datasheet of DLW43SH101XP2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=DLW43SH101XP2%23

"#" indicates a package specification code.



Specifications

	<u> </u>	
Shape	SMD	
Size Code (in mm)	4532	
Size Code (in inch)	1812	
Length	4.5mm	
Length Tolerance	±0.2mm	
Width	3.2mm	
Width Tolerance	±0.2mm	
Thickness	2.7mm	
Thickness Tolerance	±0.2mm	
Rated Current	170mA	
Derating of Rated Current	No	
Rated Voltage	50Vdc	
Withstanding Voltage	125Vdc	
DC Resistance(max.)	2Ω	
DC Resistance	2.0Ω max.	
Insulation Resistance(min.)	10ΜΩ	
Operating Temperature Range	-40°C to 125°C	
Mass(typ.)	0.17g	
Number of Circuit	1	
Common Mode Inductance	100μH-30%/+80% (at 0.1MHz)	
Operating Temperature Range(Self-temperature rise is included)	No	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



DLW43SH101XP2#


Note: This datasheet may be out of date.


Please download the latest datasheet of DLW43SH101XP2# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=DLW43SH101XP2%23

"#" indicates a package specification code.







Impedance-Frequency Characteristics

Equivalent Circuit

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

