

0.984 0.642 0.756 1.213 0.311 0.109 0.496 09 30.80 24.99 16.30 19.20 7.90 2.77 12.60 1.541 0.971 0.311 0.109 1.312 1.091 0.496 15 39.14 33.32 24.65 27.70 2.77 12.60 2.087 0.311 0.109 1.852 1.512 1.618 0.496 25 53.00 47.04 38.40 41.10 7.90 2.728 2.500 2.157 2.256 0.311 0.109 37 69.29 63.50 54.80 2.77 12.60 57.30 7.90 0.429 0.109 0.602 2.638 2.406 2.055 2.169 50 67.00 61.00 52.20 55.10 10.90 2.77

D


Ε

G

C

В

POS.



## WILL ACCEPT 28-20 AWG CONDUCTORS

**DESCRIPTION: FEMALE SOLDER CUP/STAMPED** 



THESE DRAWINGS AND SPECIFICATIONS ARE

DO NOT SCALE FROM DRAWING

NS ARE
LL NOT PAM JENKINS 9-13-05

CHECKED: DATE:

SCALE: SHEET OF

1 2

REV

6


DWG NO. 171-YYY-20YLYY1


RoHS COMPLIANT


## TOLERANCE:


ALL DIMENSIONS ARE ±0.010

## ALL CLINCH-NUTS ARE 4-40 INTERNAL THREADS











05X ..... 0.237" (BOARD SIDE) - CN10



91X ..... 0.237" BOARD SIDE

NOTE: 4-40 FEMALE SCREW LOCK IS REMOVABLE

## DO NOT SCALE FROM DRAWING



OT IE OF ON.	WAYNE ROBBINS		11-28-05		
	CHECKED:		DATE:		
	SCALE:	SHEET	OF <b>2</b>	2	REV 6
	DWG NG				

171-YYY-20YLYY1

DATE:

