



**Panasonic**  
ideas for life

**High sensitivity and low on-resistance.**  
**DIP (1 Form A) 6-pin type.**

**HE PhotoMOS**  
**(AQV25O)**



## FEATURES

- 1. Highly sensitive and low on-resistance**
- 2. Controls various types of loads such as relays, motors, lamps and solenoids.**
- 3. Optical coupling for extremely high isolation**  
5,000 Vrms I/O isolation available.
- 4. Low-level off state leakage current**
- 5. Eliminates the need for a power supply to drive the power MOSFET**  
A power supply used to drive the power MOSFET is unnecessary because of the built-in optoelectronic device. This results in easy circuit design and small PC board area.
- 6. Low thermal electromotive force (Approx. 1 µV)**

## TYPICAL APPLICATIONS

- High-speed inspection machines
- Telephone equipment
- Data communication equipment

## TYPES

### 1. I/O isolation voltage: 1,500 V AC

Output rating*		Part No.			Packing quantity	
		Through hole terminal	Surface-mount terminal			
Load voltage	Load current	Tube packing style	Tape and reel packing style		Tube	Tape and reel
			Picked from the 1/2/3-pin side	Picked from the 4/5/6-pin side		
40 V	500 mA	AQV251	AQV251A	AQV251AX	AQV251AZ	
60 V	400 mA	AQV252	AQV252A	AQV252AX	AQV252AZ	
100 V	350 mA	AQV255	AQV255A	AQV255AX	AQV255AZ	
200 V	250 mA	AQV257	AQV257A	AQV257AX	AQV257AZ	
250 V	200 mA	AQV253	AQV253A	AQV253AX	AQV253AZ	
400 V	150 mA	AQV254	AQV254A	AQV254AX	AQV254AZ	
1,000 V	30 mA	AQV259	AQV259A	AQV259AX	AQV259AZ	
1,500 V	20 mA	AQV258	AQV258A	AQV258AX	AQV258AZ	

### 2. I/O isolation voltage: Reinforced 5,000 V

Output rating*		Part No.			Packing quantity	
		Through hole terminal	Surface-mount terminal			
Load voltage	Load current	Tube packing style	Tape and reel packing style		Tube	Tape and reel
			Picked from the 1/2/3-pin side	Picked from the 4/5/6-pin side		
250 V	200 mA	AQV253H	AQV253HA	AQV253HAX	AQV253HAZ	
400 V	150 mA	AQV254H	AQV254HA	AQV254HAX	AQV254HAZ	

\*Indicate the peak AC and DC values.

Note: For space reasons, the SMD terminal shape indicator "A" and the package type indicator "X" and "Z" are omitted from the seal.

**RATING**

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item		Symbol	Type of connection	AQV251(A)	AQV252(A)	AQV255(A)	AQV257(A)	AQV253(A)	AQV254(A)	AQV259(A)	AQV258(A)	AQV253H(A)	AQV254H(A)	Remarks	
Input	LED forward current	I <sub>F</sub>		50 mA											
	LED reverse voltage	V <sub>R</sub>		5 V											
	Peak forward current	I <sub>FP</sub>		1 A										f = 100 Hz, Duty factor +0.1%	
	Power dissipation	P <sub>in</sub>		75 mW											
Output	Load voltage (peak AC)	V <sub>L</sub>		40 V	60 V	100 V	200 V	250 V	400 V	1,000 V	1,500 V	250 V	400 V		
	Continuous load current	I <sub>L</sub>		A	0.5 A	0.4 A	0.35 A	0.25 A	0.2 A	0.15 A	0.03 A	0.02 A	0.2 A	0.15 A	
				B	0.7 A	0.6 A	0.45 A	0.35 A	0.3 A	0.18 A	0.04 A	0.025 A	0.3 A	0.18 A	
				C	1.0 A	0.8 A	0.70 A	0.5 A	0.4 A	0.25 A	0.05 A	0.04 A	0.4 A	0.25 A	
	Peak load current	I <sub>peak</sub>		1.8 A	1.5 A	1.0 A	0.75 A	0.6 A	0.5 A	0.09 A	0.06 A	0.6 A	0.5 A	A connection: 100 ms (1 shot) V <sub>L</sub> = DC	
Power dissipation		P <sub>out</sub>	360 mW												
Total power dissipation		P <sub>T</sub>	410 mW												
I/O isolation voltage		V <sub>iso</sub>	1,500 V AC										5,000 V AC		
Temperature limits	Operating	T <sub>opr</sub>	−40°C to +85°C −40°F to +185°F										Non-condensing at low temperatures		
	Storage	T <sub>stg</sub>	−40°C to +100°C −40°F to +212°F												

2. Electrical characteristics (Ambient temperature: 25°C 77°F)


Item		Symbol	Type of connection	AQV251(A)	AQV252(A)	AQV255(A)	AQV257(A)	AQV253(A)	AQV254(A)	AQV259(A)	AQV258(A)	AQV253H(A)	AQV254H(A)	Condition	
Input	LED operate current	I <sub>Fon</sub>	—	0.9 mA										I <sub>L</sub> = Max.	
	Maximum			3 mA											
	LED turn off current	I <sub>loff</sub>	—	0.4 mA										I <sub>L</sub> = Max.	
	Typical			0.8 mA											
Output	LED dropout voltage	V <sub>F</sub>	—	1.25 V (1.14 V at I <sub>F</sub> = 5 mA)										I <sub>F</sub> = 50 mA	
	Maximum			1.5 V											
	On resistance	R <sub>on</sub>	A	0.6 Ω	0.74 Ω	1.8 Ω	2.6 Ω	5.5 Ω	12.4 Ω	85 Ω	345 Ω	5.5 Ω	12.4 Ω	I <sub>F</sub> = 5 mA I <sub>L</sub> = Max. Within 1 s on time	
				1 Ω	1.4 Ω	2.5 Ω	4 Ω	8 Ω	16 Ω	200 Ω	500 Ω	8 Ω	16 Ω		
		R <sub>on</sub>	B	0.3Ω	0.37 Ω	0.9 Ω	1.4 Ω	2.7 Ω	6.2 Ω	60 Ω	345 Ω	2.7 Ω	6.2 Ω	I <sub>F</sub> = 5 mA I <sub>L</sub> = Max. Within 1 s on time	
				0.5 Ω	0.7 Ω	1.25 Ω	2 Ω	4 Ω	8 Ω	100 Ω	500 Ω	4 Ω	8 Ω		
		R <sub>on</sub>	C	0.15 Ω	0.18 Ω	0.45 Ω	0.7 Ω	1.4 Ω	3.1 Ω	30 Ω	160 Ω	1.4 Ω	3.1 Ω	I <sub>F</sub> = 5 mA I <sub>L</sub> = Max. Within 1 s on time	
				0.25 Ω	0.35 Ω	0.63 Ω	1 Ω	2 Ω	4 Ω	50 Ω	250 Ω	2 Ω	4 Ω		
Transfer characteristics	Off state leakage current	Maximum	—	1 μA										I <sub>F</sub> = 0 mA V <sub>L</sub> = Max.	
	Switching speed	T <sub>on</sub>	—	1.7 ms	1.4 ms	0.9 ms	1.5 ms	0.8ms	0.8ms	0.6ms	0.35 ms	2.4ms	1.8ms	I <sub>F</sub> = 5 mA I <sub>L</sub> = Max.	
				3 ms	2 ms	3 ms	2 ms	1 ms	1 ms	4 ms	3 ms				
	Turn off time*	T <sub>off</sub>	—	0.07 ms	0.09 ms	0.1 ms	0.06 ms	0.05 ms	0.04 ms	0.06 ms	0.05 ms	I <sub>F</sub> = 5 mA I <sub>L</sub> = Max.			
				0.2 ms											
	I/O capacitance	C <sub>iso</sub>	—	1.3 pF										f = 1 MHz V <sub>B</sub> = 0 V	
	Initial I/O isolation resistance			3 pF											

Note: Recommendable LED forward current

Standard type: 5 mA

Reinforced type: 5 to 10 mA

\*Turn on/Turn off time




# HE PhotoMOS (AQV25○)

## REFERENCE DATA


### 1.-{(1)} Load current vs. ambient temperature characteristics

Allowable ambient temperature:  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$   
 $-40^{\circ}\text{F}$  to  $+185^{\circ}\text{F}$  ;  
 Type of connection: A




### 1.-{(2)} Load current vs. ambient temperature characteristics

Allowable ambient temperature:  $-40^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$   
 $-40^{\circ}\text{F}$  to  $+185^{\circ}\text{F}$  ;  
 Type of connection: A




### 2.-{(1)} On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;  
 LED current: 5 mA;  
 Continuous load current: Max. (DC)




### 2.-{(2)} On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;  
 LED current: 5 mA;  
 Continuous load current: Max. (DC)




### 2.-{(3)} On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;  
 LED current: 5 mA;  
 Continuous load current: 30 mA (DC)




### 3.-{(1)} Turn on time vs. ambient temperature characteristics

LED current: 5 mA;  
 Load voltage: Max. (DC);  
 Continuous load current: Max. (DC)




### 4.-{(1)} Turn off time vs. ambient temperature characteristics

LED current: 5 mA; Load voltage: Max. (DC);  
 Continuous load current: Max. (DC)




### 4.-{(2)} Turn off time vs. ambient temperature characteristics

Sample: AQV253H, AQV254H  
 LED current: 5 mA; Load voltage: Max. (DC);  
 Continuous load current: Max. (DC)




### 5.-{(1)} LED operate current vs. ambient temperature characteristics

Sample: AQV251, AQV252, AQV253, AQV254, AQV259; Load voltage: Max. (DC);  
 Continuous load current: Max. (DC)




### 5.-{(2)} LED operate current vs. ambient temperature characteristics

Sample: AQV253H, AQV254H;  
 Load voltage: Max. (DC);  
 Continuous load current: Max. (DC)



### 6.-{(1)} LED turn off current vs. ambient temperature characteristics


Sample: AQV251, AQV252, AQV253, AQV254, AQV259; Load voltage: Max. (DC);  
 Continuous load current: Max. (DC)



# HE Photomos (AQV25O)


## 6.-2) LED turn off current vs. ambient temperature characteristics

Sample: AQV251, AQV252, AQV253, AQV254, AQV259; Load voltage: Max. (DC); Continuous load current: Max. (DC)




## 7. LED dropout voltage vs. ambient temperature characteristics

LED current: 5 to 50 mA



## 8.-1) Current vs. voltage characteristics of output at MOS portion


Measured portion: between terminals 4 and 6; Ambient temperature: 25°C 77°F



## 8.-2) Current vs. voltage characteristics of output at MOS portion

Sample: AQV259


Measured portion: between terminals 4 and 6; Ambient temperature: 25°C 77°F



## 9.-1). Off state leakage current vs. load voltage characteristics

Sample: AQV259;


Measured portion: between terminals 4 and 6; Ambient temperature: 25°C 77°F



## 9.-2). Off state leakage current vs. load voltage characteristics


Sample: AQV254H;

Measured portion: between terminals 4 and 6; Ambient temperature: 25°C 77°F




## 10-(1). Turn on time vs. LED forward current characteristics

Measured portion: between terminals 4 and 6; Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




## 10-(2). Turn on time vs. LED forward current characteristics

Measured portion: between terminals 4 and 6; Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




## 11-(1). Turn off time vs. LED forward current characteristics

Measured portion: between terminals 4 and 6; Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




## 11-(2). Turn off time vs. LED forward current characteristics

Measured portion: between terminals 4 and 6; Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F



## 12.-1) Output capacitance vs. applied voltage characteristics

Measured portion: between terminals 4 and 6; Frequency: 1 MHz; Ambient temperature: 25°C 77°F



## 12.-2) Output capacitance vs. applied voltage characteristics

Sample: AQV259; Measured portion: between terminals 4 and 6; Frequency: 1 MHz; Ambient temperature: 25°C 77°F

