



### Normally closed SOP6-pin type of 400V load voltage

PhotoMOS<sup>®</sup>  
GU SOP 1 Form B  
(AQV414S)




RoHS compliant

## FEATURES


### 1. Miniature SOP6-pin package

The device comes in a small SOP measuring (W) 4.4 × (L) 6.3 × (H) 2.1 mm (W) .173 × (L) .248 × (H) .083 inch approx. 25% of the volume and 50% of the footprint size of DIP type.



### 2. Low on-resistance (Typ. 26 Ω) for normally-closed type

This has been achieved thanks to the built-in MOSFET processed by our proprietary method, DSD (Double-Diffused and Selective Doping) method.



### 3. Controls low-level analog signals

PhotoMOS feature extremely low closed-circuit offset voltage to enable control of low-level analog signals without distortion.

### 4. Low-level off state leakage current of max. 1 μA

## TYPICAL APPLICATIONS

- Telephones
- Measuring instruments
- Computers
- Industrial robots
- High-speed inspection machines

## TYPES



	Output rating*		Package	Part No.			Packing quantity	
	Load voltage	Load current		Tube packing style	Tape and reel packing style		Tube	Tape and reel
					Picked from the 1/2/3-pin side	Picked from the 4/5/6-pin side		
AC/DC dual use	400V	100mA	SOP6-pin	AQV414S	AQV414SX	AQV414SZ	1 tube contains: 75 pcs. 1 batch contains: 1,500 pcs.	1,000 pcs.

\* Indicate the peak AC and DC values.

Note: For space reasons, only "V41S" is marked on the product. The two initial letters of the part number "AQ" and the packing style indicator "X" or "Z" have been omitted.

## RATING


### 1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)

Item		Symbol	Type of connection	AQV414S	Remarks
Input	LED forward current	I <sub>F</sub>		50 mA	
	LED reverse voltage	V <sub>R</sub>		5 V	
	Peak forward current	I <sub>FP</sub>		1 A	f = 100 Hz, Duty factor = 0.1%
	Power dissipation	P <sub>in</sub>		75 mW	
Output	Load voltage (peak AC)	V <sub>L</sub>			400 V
	Continuous load current	I <sub>L</sub>	A	0.10 A	A connection: Peak AC, DC B, C connection: DC
			B	0.11 A	
			C	0.12 A	
	Peak load current	I <sub>peak</sub>		0.3 A	A connection: 100 ms (1 shot) V <sub>L</sub> = DC
	Power dissipation	P <sub>out</sub>		450 mW	
	Total power dissipation			P <sub>T</sub>	500 mW
I/O isolation voltage		V <sub>iso</sub>		1,500 Vrms	
Ambient temperature	Operating	T <sub>opr</sub>		−40 to +85°C −40 to +185°F	(Non-icing at low temperatures)
	Storage	T <sub>stg</sub>	−40 to +100°C −40 to +212°F		

### 2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item	Symbol	Type of connection	AQV414S	Condition
Input	LED operate (OFF) current	I <sub>Off</sub>	—	I <sub>L</sub> = Max.
	LED reverse (ON) current	I <sub>Fon</sub>	—	I <sub>L</sub> = Max.
Output	LED dropout voltage	V <sub>F</sub>	—	I <sub>F</sub> = 50 mA
	On resistance	R <sub>on</sub>	A	I <sub>F</sub> = 0 mA I <sub>L</sub> = Max. Within 1 s
		R <sub>on</sub>	B	I <sub>F</sub> = 0 mA I <sub>L</sub> = Max. Within 1 s
		R <sub>on</sub>	C	I <sub>F</sub> = 0 mA I <sub>L</sub> = Max. Within 1 s
Transfer characteristics	Off state leakage current	I <sub>Leak</sub>	—	I <sub>F</sub> = 5 mA, V <sub>L</sub> = Max.
	Operate (OFF) time*	T <sub>off</sub>	—	I <sub>F</sub> = 0 mA → 5 mA V <sub>L</sub> = Max.
	Reverse (ON) time*	T <sub>on</sub>	—	I <sub>F</sub> = 5 mA → 0 mA V <sub>L</sub> = Max.
	I/O capacitance	C <sub>iso</sub>	—	f = 1 MHz V <sub>B</sub> = 0 V
	Initial I/C isolation resistance	R <sub>iso</sub>	—	500 V DC

\*Operate/Reverse time



### 3. Recommended operating conditions (Ambient temperature: 25°C 77°F)

Please use under recommended operating conditions to obtain expected characteristics.

Item	Symbol	Min.	Max.	Unit
LED current	I <sub>F</sub>	5	30	mA
AQV414S Load voltage (Peak AC)	V <sub>L</sub>	—	320	V
Continuous load current (A connection)	I <sub>L</sub>	—	0.1	A

■ These products are not designed for automotive use.


If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

## REFERENCE DATA

### 1. Load current vs. ambient temperature characteristics


Allowable ambient temperature:  $-40$  to  $+85^{\circ}\text{C}$   
 $-40$  to  $+185^{\circ}\text{F}$

Type of connection: A




### 2. On resistance vs. ambient temperature characteristics

Measured portion: between terminals 4 and 6;  
 LED current: 0 mA;  
 Continuous load current: 100 mA (DC)




### 3. Operate (OFF) time vs. ambient temperature characteristics

LED current: 5 mA;  
 Load voltage: 400 V (DC);  
 Continuous load current: 100 mA (DC)




### 4. Reverse (ON) time vs. ambient temperature characteristics

LED current: 50 mA;  
 Load voltage: 400 V (DC);  
 Continuous load current: 100 mA (DC)




### 5. LED operate (OFF) current vs. ambient temperature characteristics

Load voltage: 400 V (DC);  
 Continuous load current: 100 mA (DC)




### 6. LED reverse (ON) current vs. ambient temperature characteristics

Load voltage: 400 V (DC);  
 Continuous load current: 100 mA (DC)




### 7. LED dropout voltage vs. ambient temperature characteristics

LED current: 5 to 50 mA




### 8. Current vs. voltage characteristics of output at MOS portion

Measured portion: between terminals 4 and 6;  
 Ambient temperature:  $25^{\circ}\text{C}$   $77^{\circ}\text{F}$




### 9. Off state leakage current vs. load voltage characteristics

Measured portion: between terminals 4 and 6;  
 LED current: 5 mA;  
 Ambient temperature:  $25^{\circ}\text{C}$   $77^{\circ}\text{F}$




10. Operate (OFF) time vs. LED forward current characteristics

Measured portion: between terminals 4 and 6;  
Load voltage: 400 V (DC); Continuous load current:  
100 mA (DC); Ambient temperature: 25°C 77°F




11. Reverse (ON) time vs. LED forward current characteristics

Measured portion: between terminals 4 and 6;  
Load voltage: 400 V (DC); Continuous load current:  
100 mA (DC); Ambient temperature: 25°C 77°F



12. Output capacitance vs. applied voltage characteristics

Measured portion: between terminals 4 and 6;  
LED current: 5 mA; Frequency: 1 MHz;  
Ambient temperature: 25°C 77°F



"PhotoMOS®", "PhotoMOS" and "PHOTOMOS" are registered trademarks of Panasonic Corporation.

\*Recognized in Japan, the United States, all member states of European Union and other countries.

Please contact .....

**Panasonic Corporation**

Electromechanical Control Business Division

■ 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8506, Japan  
[industrial.panasonic.com/ac/e/](http://industrial.panasonic.com/ac/e/)

**Panasonic®**

©Panasonic Corporation 2017

ASCTB139E 201703-T

Specifications are subject to change without notice.