

**Panasonic**  
ideas for life

**High capacity  
PhotoMOS Relay.  
(Load current Max. 4A)  
DC load type is available.**


**Power PhotoMOS  
(AQZ10○, 20○)**

## FEATURES


1. **High capacity PhotoMOS Relay in a compact and slim 4-pin SIL**
2. **Extremely low ON resistance**
3. **Control low-level signal**  
Power Photo MOS relays feature extremely low closed-circuit offset voltage to enable control of low-level analog signals without distortion.
4. **Low-level off state leakage current**
5. **High I/O isolation voltage 2,500 V**
6. **Eliminates the need for a counter electromotive protection diode in the drive circuit on the input side**
7. **Eliminate the need for a power supply to drive the power MOSFET**
8. **PC board layout is simplified**
9. **No restriction on mounting direction**
10. **Varistor incorporated type is also available.**

## TYPICAL APPLICATIONS


- High-speed inspection machines
- IC checker
- NC machine, Robots
- Office machines
- Telecommunication
- Automotive



mm inch



AC/DC type



DC type

## TYPES

### 1. AC/DC type

Output rating		Part No.	Packing quantity	
Load voltage	Load current		Inner carton	Outer carton
60 V	3.0 A	AQZ202	25 pcs.	500 pcs.
100 V	2.0 A			
200 V	1.0 A			
400 V	0.5 A			

### 2. DC type

Output rating		Part No.	Packing quantity	
Load voltage	Load current		Inner carton	Outer carton
60 V	4.0 A	AQZ102	25 pcs.	500 pcs.
100 V	2.6 A			
200 V	1.3 A			
400 V	0.7 A			

Notes: Load voltage and current of AC/DC type: Peak AC/DC.

Load voltage and current of DC type: DC

# Power PhotoMOS (AQZ10○, 20○)

## RATING

### 1. AC/DC type

1) Absolute maximum ratings (Ambient temperature: 25°C 77°F)


Item		Symbol	AQZ202	AQZ205	AQZ207	AQZ204	Remarks
Input	LED forward current	I <sub>F</sub>	50 mA				
	LED reverse voltage	V <sub>R</sub>	5 V				
	Peak forward current	I <sub>FP</sub>	1 A				f = 100 Hz, Duty factor = 0.1%
	Power dissipation	P <sub>in</sub>	75 mW				
Output	Load voltage (Peak AC)	V <sub>L</sub>	60 V	100 V	200 V	400 V	
	Continuous load current	I <sub>L</sub>	3.0 A	2.0 A	1.0 A	0.5 A	
	Peak load current	I <sub>peak</sub>	9.0 A	6.0 A	3.0 A	1.5 A	100 ms (1 shot), V <sub>L</sub> = DC
	Power dissipation	P <sub>out</sub>	1.6 W				
Total power dissipation		P <sub>T</sub>	1.6 W				
I/O isolation voltage		V <sub>iso</sub>	2,500 V AC				
Temperature limits	Operating	T <sub>opr</sub>	−40°C to +85°C −40°F to +185°F				Non-condensing at low temperatures
	Storage	T <sub>stg</sub>	−40°C to +100°C −40°F to +212°F				

2) Electrical characteristics (Ambient temperature: 25°C 77°F)

Item		Symbol	AQZ202	AQZ205	AQZ207	AQZ204	Condition	
Input	LED operate current		Typical Maximum	I <sub>Fon</sub>	1.0 mA		I <sub>L</sub> = 100 mA V <sub>L</sub> = 10 V	
					3.0 mA			
	LED turn off current		Minimum Typical	I <sub>loff</sub>	0.4 mA		I <sub>L</sub> = 100 mA V <sub>L</sub> = 10 V	
					0.9 mA			
Output	LED dropout voltage		Typical Maximum	V <sub>F</sub>	1.25 V (1.16 V at I <sub>F</sub> = 10 mA)		I <sub>F</sub> = 50 mA	
					1.5 V			
	On resistance		Typical Maximum	R <sub>on</sub>	0.11 Ω	0.23 Ω	0.7 Ω	I <sub>F</sub> = 10 mA I <sub>L</sub> = Max. Within 1 s on time
					0.18 Ω	0.34 Ω	1.1 Ω	3.2 Ω
Transfer characteristics	Off state leakage current		Maximum	—	10 μA		I <sub>F</sub> = 0 mA V <sub>L</sub> = Max.	
	Switching speed	Turn on time*	Typical	T <sub>on</sub>	2.46 ms	2.40 ms	1.12 ms	I <sub>F</sub> = 10 mA I <sub>L</sub> = 100 mA V <sub>L</sub> = 10 V
			Maximum		5.0 ms			
			Typical		5.64 ms	5.65 ms	2.57 ms	I <sub>F</sub> = 5 mA I <sub>L</sub> = 100 mA V <sub>L</sub> = 10 V
			Maximum		10.0 ms			
	Turn off time*	Typical	T <sub>off</sub>		0.22 ms	0.21 ms	0.10 ms	I <sub>F</sub> = 5 mA or 10 mA I <sub>L</sub> = 100 mA V <sub>L</sub> = 10 V
		Maximum			0.08 ms		3.0 ms	
	I/O capacitance		C <sub>iso</sub>	0.8 pF				f = 1 MHz V <sub>B</sub> = 0 V
				1.5 pF				
	Initial I/O isolation resistance		Minimum	R <sub>iso</sub>	1,000 MΩ		500 V DC	
	Maximum operating speed		Maximum	—	0.5 cps		I <sub>F</sub> = 10 mA Duty factor = 50% I <sub>L</sub> = Max., V <sub>L</sub> = Max.	
Vibration resistance		Minimum	—	10 to 55 Hz at double amplitude of 3 mm		2 hours for 3 axes		
Shock resistance		Minimum	—	4,900 m/s <sup>2</sup> {500 G}1 ms		3 times for 3 axes		

Note: Recommendable LED forward current I<sub>F</sub> = 5 to 10 mA.

\*Turn on/off time



# Power PhotoMOS (AQZ10○, 20○)

## 2. DC type

1) Absolute maximum ratings (Ambient temperature: 25°C 77°F)


	Item	Symbol	AQZ102	AQZ105	AQZ107	AQZ104	Remarks
Input	LED forward current	$I_F$		50 mA			
	LED reverse voltage	$V_R$		5 V			
	Peak forward current	$I_{FP}$		1 A			$f = 100 \text{ Hz, Duty factor} = 0.1\%$
	Power dissipation	$P_{in}$		75 mW			
Output	Load voltage (DC)	$V_L$	60 V	100 V	200 V	400 V	
	Continuous load current (DC)	$I_L$	4.0 A	2.6 A	1.3 A	0.7 A	
	Peak load current	$I_{peak}$	9.0 A	6.0 A	3.0 A	1.5 A	100 ms (1 shot), $V_L = \text{DC}$
	Power dissipation	$P_{out}$		1.35 W			
Total power dissipation		$P_T$		1.35 W			
I/O isolation voltage		$V_{iso}$		2,500 V AC			
Temperature limits	Operating	$T_{opr}$	-40°C to +85°C -40°F to +185°F			Non-condensing at low temperatures	
	Storage	$T_{stg}$	-40°C to +100°C -40°F to +212°F				

2) Electrical characteristics (Ambient temperature: 25°C 77°F)

	Item	Symbol	AQZ102	AQZ105	AQZ107	AQZ104	Condition
Input	LED operate current	$I_{Fon}$	1.0 mA			$I_L = 100 \text{ mA}$	
			3.0 mA			$V_L = 10 \text{ V}$	
	LED turn off current	$I_{Foff}$	0.4 mA			$I_L = 100 \text{ mA}$	
			0.9 mA			$V_L = 10 \text{ V}$	
Output	LED dropout voltage	$V_F$	1.25 V (1.16 V at $I_F = 10 \text{ mA}$ )				$I_F = 50 \text{ mA}$
			1.5 V				
	On resistance	$R_{on}$	0.05 Ω	0.081 Ω	0.34 Ω	1.06 Ω	$I_F = 10 \text{ mA}$
			0.09 Ω	0.17 Ω	0.55 Ω	1.6 Ω	$I_L = \text{Max.}$ Within 1 s on time
Transfer characteristics	Off state leakage current	—	10 μA				$I_F = 0 \text{ mA}$ $V_L = \text{Max.}$
	Switching speed	$T_{on}$	1.66 ms	1.89 ms	0.83 ms	1.01 ms	$I_F = 10 \text{ mA}$ $I_L = 100 \text{ mA}$ $V_L = 10 \text{ V}$
			5.0 ms				
			3.79 ms	4.50 ms	1.75 ms	2.34 ms	$I_F = 5 \text{ mA}$ $I_L = 100 \text{ mA}$ $V_L = 10 \text{ V}$
			10.0 ms				
	Turn off time*	$T_{off}$	0.15 ms	0.19 ms	0.08 ms	0.08 ms	$I_F = 5 \text{ mA or } 10 \text{ mA}$
			3.0 ms				$I_L = 100 \text{ mA}$ $V_L = 10 \text{ V}$
	I/O capacitance	$C_{iso}$	0.8 pF				$f = 1 \text{ MHz}$ $V_B = 0 \text{ V}$
	Initial I/O isolation resistance		1.5 pF				
	Maximum operating speed	Maximum	—	0.5 cps			$I_F = 10 \text{ mA}$ Duty factor = 50% $I_L \times V_L = 200 \text{ (VA)}$
Vibration resistance		Minimum	—	10 to 55 Hz at double amplitude of 3 mm			2 hours for 3 axes
Shock resistance		Minimum	—	4,900 m/s <sup>2</sup> {500 G} 1 ms			3 times for 3 axes

Note: Recommendable LED forward current  $I_F = 5$  to 10 mA.


\*Turn on/off time






# Power PhotoMOS (AQZ10○, 20○)


7.-(2) LED turn off current vs. ambient temperature characteristics (DC type)  
Load voltage: 10 V (DC);  
Continuous load current: 100 mA (DC)




8. LED dropout voltage vs. ambient temperature characteristics  
Sample: all types; LED current: 5 to 50 mA




9.-(1) Current vs. voltage characteristics of output at MOS portion (AC/DC type)  
Ambient temperature: 25°C 77°F




9.-(2) Current vs. voltage characteristics of output at MOS portion (DC type)  
Ambient temperature: 25°C 77°F




10. Off state leakage current vs. load voltage characteristics  
Ambient temperature: 25°C 77°F




11.-(1) Turn on time vs. LED forward current characteristics (AC/DC type)  
Load voltage: 10 V (DC);  
Continuous load current: 100 mA (DC);  
Ambient temperature: 25°C 77°F




11.-(2) Turn on time vs. LED forward current characteristics (DC type)  
Load voltage: 10 V (DC);  
Continuous load current: 100 mA (DC);  
Ambient temperature: 25°C 77°F




12.-(1) Turn off time vs. LED forward current characteristics (AC/DC type)  
Load voltage: 10 V (DC);  
Continuous load current: 100 mA (DC);  
Ambient temperature: 25°C 77°F




12.-(2) Turn off time vs. LED forward current characteristics (DC type)  
Measured portion: between terminals 4 and 6;  
Load voltage: 10 V (DC);  
Continuous load current: 100 mA (DC);  
Ambient temperature: 25°C 77°F




13.-(1) Turn on time vs. load voltage characteristics (Load voltage: 60, 100 V type)  
LED current: 10 mA;  
Continuous load current: 100 mA;  
Ambient temperature: 25°C 77°F



13.-(2) Turn on time vs. load voltage characteristics (Load voltage: 200, 400 V type)  
LED current: 10 mA;  
Continuous load current: 100 mA;  
Ambient temperature: 25°C 77°F




14.-(1) Turn on time vs. load current characteristics (Load voltage: 60, 100 V type)  
LED current: 10 mA;  
Load voltage: 10 V (DC);  
Ambient temperature: 25°C 77°F




# Power PhotoMOS (AQZ10○, 20○)


14.-(2) Turn on time vs. load current characteristics (Load voltage: 200, 400 V type)  
LED current: 10 mA;  
Load voltage: 10 V (DC);  
Ambient temperature: 25°C 77°F




16.-(1) Turn off time vs. load current characteristics (Load voltage: 60, 100 V type)  
LED current: 10 mA;  
Load voltage: 10 V (DC);  
Ambient temperature: 25°C 77°F




15.-1) Turn off time vs. load voltage characteristics (Load voltage: 60, 100 V type)  
LED current: 10 mA;  
Continuous load current: 100 mA;  
Ambient temperature: 25°C 77°F




15.-2) Turn off time vs. load voltage characteristics (Load voltage: 200, 400 V type)  
LED current: 10 mA;  
Continuous load current: 100 mA;  
Ambient temperature: 25°C 77°F



18.-1) Output capacitance vs. applied voltage characteristics (AC/DC type)  
Frequency: 1 MHz;  
Ambient temperature: 25°C 77°F





18.-2) Output capacitance vs. applied voltage characteristics (DC type)  
Frequency: 1 MHz;  
Ambient temperature: 25°C 77°F





## ACCESSORY

### Socket




PA1a-PS




PA1a-PS-H

PC board pattern  
(BOTTOM VIEW)  
Standard type



Self clinching type



Tolerance: ±0.1 ±.004