Search Results

Evaluate
- FAQ's
- Line Cards
- PDFCable Access ..

Design a Solution
- Part Drawings
- PDFBridle Ring..
- Specification Sheets
- PDFCable Access ..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'BR-2.0-TW'**

Your search criteria matched only one product, shown below

BR-2.0-TW

• Multiple diameters, thread sizes, and configurations
• Threaded and non -threaded sizes are compatible with spring steel clip (BR -MPCL) clamp providing a solid securing point for the bridle ring
• Other unique labor saving assemblies differentiate from competition – including pre - assemblies with powder actuated fasteners, toggle wings, and clearance holes for user supplied fasteners

Part Number	BR-2.0-TW
RoHS Compliancy Status	Compliant
Part Description	Bridle ring, 2.00" dia., with integrated toggle screw.
Material	Low carbon steel with bright zinc electroplate
Max. Bundle Capacity (In.)	2.00
Max. Bundle Capacity (mm)	51
Overall Height (In.)	6.4
Overall Height (mm)	163
Pricing Description	Bridle Ring, 2.00" Dia., w/ Integrated Toggle Screw
Ring Size	2"
Thread size	Includes integrated toggle screw
Min. Order UOM	PC
Min. Order Qty.	25
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2010, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy