



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'CD9-12A'

Your search criteria matched only one product, shown below

CD9-12A



Reel Smart™ Installation Requirements.
All tooling information, including crimp shut height dimension, is included on the product reel label.

	Part Number	CD9-12A
	RoHS Compliancy Status	RoHS directive is not applicable
	Part Description	Die Insert for CA9 Applicator
	60/40 Solder Slug Dia. (In.)	.125
	60/40 Solder Slug Dia. (mm)	3.18
	CE Compliant	No
	CE Marking	No
	Panduit Color Code	Red
	Pricing Description	Die Insert, for use with CA9 Applicator, to terminate PANDUIT reeled disconnects
	Wire Insulation Strain Relief	DISCOGRIP™ Insulation Crimp
	Wire Range	22 – 18
	Wire Range (mm ²)	0.5 – 1.0
	Min. Order UOM	PC
	Min. Order Qty.	1
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.