Search Results

Evaluate
- FAQ's
- Selection Guides
- PDF Convenience ..

Design a Solution
- Part Drawings
- PDF Male Coupler..

How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'DNF14-250FIM-E'**

Your search criteria matched only one product, shown below

DNF14-250FIM-E

- Disconnect can be inserted and removed from the male tab without the use of tools for lower installed cost
- Fully insulated design provides protection from electrical shorts
- Internal barrel serrations assure good wire contact and maximum tensile strength
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection
- Coupler, male, and female parts sold separately
- UL Flammability UL 94V -2/HB, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 310

Part Number	DNF14-250FIM-E
RoHS Compliancy Status	Compliant
Part Description	Male Disconnect, nylon fully insulated, 16– 14 AWG, .250 x .032 tab size.
Product Type	Disconnects
CSA Certified	Yes
UL Listed	Yes
Height (In.)	0.27
Height (mm)	6.9
Length (In.)	0.90
Length (mm)	22.9
Width (In.)	0.42
Width (mm)	10.7
CE Compliant	No
Insulation	Nylon
Max. Ins.	0.158
Max. Ins. (mm)	4.08
Panduit Color Code	Blue
Plating Type	Nickel
Pricing Description	Terminal Convenience Package
Tab Size (In.)	0.250 x 0.032
Tab Size (mm)	6.3 x 0.8
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)
Tool	CT-600-A, CT-1525‡CT-100, CT-600-A, CT-1525‡, CT-2500‡
Type	Male
Wire Range	16 – 14 AWG
Wire Range (mm²)	1.5 – 2.5
Min. Order UOM	PC
Min. Order Qty.	20
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy