

Search Results

- Evaluate
- Advertisements
 - PDFHighest Perf..
 - FAQ's
 - Product Bulletins
 - PDFDirect Buria..
 - Videos
 - WMV-Panduit Comp..
- Design a Solution
- Catalog Cut Sheet
 - PDFGCC6X61/01/ ..
 - Part Drawings
 - PDFGrounding Cr..
 - DWG-2-D cad for ..
 - DWG-3-D cad for ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor
- Install & Maintain
- Installation Instructions
 - PDFDirect Buria..

Home > Products Overview > Search Results >

Current refinements (click  to remove) [Search Tips](#)

 **Text Search: 'GCC6X6500-1/0'**

Your search criteria matched only one product, shown below

GCC6X6500-1/0



- Only a single die required to crimp each element, which speeds installation and reduces costs
- Wide range-taking ability and multi-conductor design provide flexibility with a minimum number of parts, allowing for conductor to conductor, conductor to rebar, and conductor to ground rod applications
- Designed for the enhanced crimp process using patent pending technology meets IEEE Std 837™ – 2002
- Slotted design allows quick and easy assembly of conductor to connector using Panduit cable ties, included
- Pre-applied conductive antioxidant compound ensures a high quality mechanical and electrical bond, speeding installation
- Color-coded and marked with Panduit die index numbers for proper crimp die selection
- UL 467 Listed and CSA 22.2 Certified for grounding and bonding suitable for direct burial in earth or concrete when crimped with Panduit or industry standard crimping tools and Panduit dies

• Complies with vibration tests per MIL -STD-202G (METHOD 201A)	
▪ Part Number	GCC6X65001/0
▪ RoHS Compliancy Status	Compliant
▪ Part Description	Grounding cross connector for 250 – 500 kcmil (150– 240mm²) and #6 SOL-1/0 STR AWG (15 – 50mm²) wire size.
▪ CSA Certified	Yes
▪ UL Listed	Yes
▪ CE Compliant	No
▪ Copper Conductor Size Range (B) (mm²)	(16 – 50)
▪ Copper Lightning Conductor Size Range (A)	—
▪ Ground Rod Size A (In.)	1/2 – 3/4
▪ Ground Rod Size A (mm)	(12.7 – 19.1)
▪ Height - A	2.48 (63.0mm)
▪ Height - B	1.94 (49.3mm)
▪ Length - A	1.00 (25.4mm)
▪ Length - B	1.00 (25.4mm)
▪ Panduit Color Code	Blue
▪ Panduit Die Index No.	PG50
▪ Pricing Description	Ground Cross Connector for 250– 500 kcmil (150- 240mm²) and #6 SOL– 1/0 STR AWG (15– 50mm²)
▪ Rebar Size A (In.)	5/8 – 3/4, #5 – #6
▪ Rebar Size A (mm)	(15.9 – 19.1), (#16 – #19)
▪ Width - A	1.32 (33.5mm)
▪ Width - B	1.09 (27.7mm)
▪ Min. Order UOM	PC
▪ Min. Order Qty.	1
▪ BOM Qty. (# of Pkgs.)	0
▪ Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.