PANDUIT® building a smarter, unified business foundation
Connect. Manage. Automate.

Unified Physical Infrastructure™

Worldwide |

| Industries | Solutions | Services | Software | Products | Partners | Support | About Us |

-Search-   Entire Site   GO

Search Results

Evaluate
- FAQ's
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove)   Search Tips ?

☒ **Text Search: 'NKSOPBUY'**

Your search criteria matched only one product, shown below

NKSOPBUY

- TIA/EIA-604 FOCIS-6 compliant connectors
- Exceed TIA/EIA-568-B.3 requirements
- Insertion loss: .1dB typical (multimode), .2dB typical (singlemode)
- Return loss: >20dB (multimode), >40dB (singlemode)
- RJ45 small form factor duplex plug
- Non-optical disconnect maintains data transmission under tensile loads
- Each duplex plug includes housing, insert, two ferrule assemblies, two crimp sleeves, one boot for 3mm jacketed cable and two dust caps
- Fiber cable type: tight-buffered recommended
- Fiber cable size: 3.0mm jacketed cable or 1.6mm - 2.0mm jacketed cable (noted in part description)
- Ferrule type: 2.5mm zirconia ceramic (highest durability for repeated matings)
- Field polish termination -- *PANDUIT*® recommends anaerobic adhesive
- Use Field Polish Termination Kit (FJKITG)

• Part Number	NKSOPBUY
• RoHS Compliancy Status	Compliant
• Part Description	NetKey® FJ® singlemode duplex plug.
• Product Type	Fiber Optic Adapter Modules
• Color	Blue
• CE Compliant	No
• Pricing Description	NetKey Opti-Plug Singlemode Fiber Connector
• Min. Order UOM	PC
• Min. Order Qty.	1
• BOM Qty. (# of Pkgs.)	0
• Add to Favorite Product List	☐

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.