Search Results

Evaluate
- FAQ's
Design a Solution
- Catalog Cut Sheet
- PDF-PCSBMT2/0-4- ..
- Part Drawings
- PDF-Multi-Tap Co..
How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Current refinements (click ☒ to remove) Search Tips

☒ **Text Search: 'PCSBMT2/0-12-1Y'**

Your search criteria matched only one product, shown below

PCSBMT2/0-12-1Y

For Use with Aluminum or Copper Code Conductors
• Flexible design – can be used as a tap, splice, or dead end connector
• Body made from high strength, extruded aluminum alloy to provide premium electrical and mechanical performance
• Two isolated mounting holes at either end of connector facilitate direct mounting using 1/4 inch bolts
• Insulated with clear PVC to eliminate the need for taping and allow for visual inspection of the complete conductor insertion
• Each port pre-filled with oxide inhibiting joint compound seals out air and moisture to deter surface oxidation
• Wide wire range -taking capability minimizes inventory requirements
• Dual-sided entry allows offset and opposite entry for primary and secondary conductors
• Plated steel or aluminum set screw provides high strength, durable electrical contact between conductor and connector
• UL Listed and CSA Certified for use up to 600 V and temperature rated 90°C

Part Number	PCSBMT2/0-12-1Y
RoHS Compliancy Status	Compliant
Note	PCSBMT2/0-12-1Y replaces PCSBMT2/0-12-1
Part Description	Multi-Tap Connector, double-sided mounting, 12 ports.
Material	Aluminum, Insulated with Clear PVC
CSA Certified	Yes
UL Listed	Yes
Depth (mm)	243.3
Height (In.)	1.50
Height (mm)	38.1
Length (In.)	9.58
Length (mm)	243.3
Width (In.)	1.56
Width (mm)	39.6
Stud Hole Size (In.)	1/4
Aluminum or Copper Conductor Size Range	2/0 – #14 AWG STR #10 – #14 AWG SOL
CE Compliant	No
Hex Key Size (In.)	1/2
Mounting Hole Spacing (In.)	8.99
Mounting Hole Spacing (mm)	228.3
No. of Ports	12
Pricing Description	Multi-Tap Connector, DoubleSided, Clear Insul., w/Mount Holes, 12 Ports, 2/0 #14 STR
Spacing (In.)	0.67
Tightening Torque (In-Lbs)	120
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	e

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Copyright © 1995-2011, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy