



Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor


Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips

Text Search: 'PVT-238-Q'

Your search criteria matched only one product, shown below

PVT-238-Q



All tags have a write-on surface that accepts pen pencil or marker pens. Can be permanently marked with *Panduit*®Marker Pens

- Meet OSHA Standard 1910.147 requirements for tagout applications
- Semi-rigid plastic tags are 3.00" (76.00mm) W x 5.75" (146.00mm) H with a .38" (9.00mm) brass grommet for greater strength and increased durability
- Tags can be attached with a lockout device or with a *PANDUIT* PLT2S nylon tie (50 lb. loop tensile strength) supplied with each tag
- PVT-* Package consists of five tags and five cable ties
- PVT-*-Q Package consists of 25 tags and 25 cable ties
- Can be clearly identified with *PANDUIT* permanent marking pens

	Part Number	PVT-238-Q
	RoHS Compliancy Status	Compliant
	Part Description	Plastic Tag, 3.00" x 5.75", ' _____ Volts', 25/Pk
	Material	GMV5 SemiRigid Plastic
	Height (In.)	5.75
	Height (mm)	146.0
	Width (In.)	3.00
	Width (mm)	76.0
	Color (Legend/Background)	Red and Black/White
	Legend	_____ VOLTS
	Marker / Tag Style	A
	Pricing Description	Plastic Tag, 'Danger _____ Volts', 25 tags & ties/pk, RB/WH
	Tags & Ties Per Pkg.	25
	Min. Order UOM	PK
	Min. Order Qty.	1
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.