



Search Results

- Evaluate
- FAQ's
 - Selection Guides
 - PDFPAN-LUG Alum ..
- Design a Solution
- Part Drawings
 - PDFAluminum Spl ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

[Home](#) > [Products Overview](#) > [Search Results](#) >

Current refinements (click to remove) [Search Tips](#) Within Results

Text Search: 'SBA4-C'

Your search criteria matched only one product, shown below

SBA4C



For Use with Copper and Aluminum Code Conductors

- Made from lightweight, durable aluminum alloy to resist corrosion and provide premium electrical and mechanical performance
- Dual rated for use with aluminum to aluminum, aluminum to copper, and copper to copper conductor combinations
- Tin-plated to inhibit corrosion and oxidation
- Wide wire range -taking capability minimizes inventory requirements
- True hex design for body and nut hex provides correct fit with socket, box, or open end wrenches resulting in proper torquing of electrical connection
- Free floating pressure bar separates conductors of dissimilar materials for secure connection on a full range of conductor combinations
- UL Listed and CSA Certified for use up to 600 V and UL temperature rated 90° C

Part Number	SBA4-C
RoHS Compliancy Status	Compliant
Part Description	Aluminum dual rated split bolt connector, type SBA.
Product Type	Mechanical Connectors- Split Bolt
CSA Certified	Yes
UL Listed	Yes
Length (In.)	1.38
Length (mm)	35.1
Max Run to Max Tap	#4 STR– #4 STR
Max Run to Min Tap	#4 STR– #10 SOL
Min Run to Min Tap	#8 SOL – #10 SOL
Body Hex	.62
Inside Diameter (In.)	.26
Nut Hex	.81
Pricing Description	Split Bolt, Aluminum, #4 STR #10 SOL AWG, Dual Rated
Tightening Torque (InLbs)	165
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.