



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
 - PDFCopper Butt ..
- How to Buy
- Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'SCS6-L'

Your search criteria matched only one product, shown below

SCS6-L



For Use with Stranded Copper Conductors

- Color-coded barrels marked with *PANDUIT* and specified competitor die index numbers for proper crimp die selection
- Internal wire stops to prevent over -insertion of conductor
- Tin-plated to inhibit corrosion
- UL Listed and CSA Certified to 35 KV** and temperature rated to 90°C when crimped with *PANDUIT* and specified competitor crimping tools and dies
- UL Listed and CSA Certified for wide wire range -taking capability when crimped with *PANDUIT*® *Uni-Die*™ Dieless Crimping Tools‡
- **Tested by Telcordia– meets NEBS Level 3**
- American Bureau of Shipping Approved

	Part Number	SCS6-L
	RoHS Compliancy Status	Compliant
	Part Description	Copper Butt Splice, standard barrel, #6 AWG wire.
	Product Type	Compression Connectors- Splices
	CSA Certified	Yes
	UL Listed	Yes
	Length (In.)	1.75
	Length (mm)	44.4
	Copper Conductor Size	#6 AWG
	Barrel O.D.	.31
	Barrel I.D.	.22
	Panduit Color Code	Blue
	Panduit Die Index No.	P24
	Pricing Description	Copper Compression Butt Splice, Standard Barrel, #6 AWG
	Wire Strip Length (In.)	13/16
	Min. Order UOM	PC
	Min. Order Qty.	1
	Burndy Die Index No.	7
	T&B Die Index No.	24
	BOM Qty. (# of Pkgs.)	0
	Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.