


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORPORATION.

PANDUIT PART NO.	BUNDLE DIA. MIN - MAX.	DIMENSIONS						MATERIAL	COLOR	WEIGHT grams 100 pcs
		'A'	'B'	'C'	'D'	'E'				
SICW04B08-...30	0 - 4.2	7.0	4.2	10	5	11.3		HEAT STABILIZED NYLON 6/6	BLACK	25



NOTES:

1. SEE CURRENT PRICE SHEET FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE, AND COLOR.
2. (*) DIMENSIONAL VARIANCE IS POSSIBLE DUE TO MOLDING PROCESS RELATED SINK MARKS.
3. APPLICATION SPECIFICATION:
HOLE DIAMETER: 6.3 - 6.7 mm
PANEL THICKNESS: 0.8 - 3.2 mm
4. (**) DIMENSION REFERS TO THE PART WHEN IT IS CLOSED.

CAD FILENAME/LAYERS		G01932BL_PB_SICW04B08_02	
PANDUIT		CORP.	
		TINLEY PARK, ILLINOIS	
SNAP IN CLIP			
Unless otherwise specified, all dimensions are metric tolerance; $\pm 0.5\text{mm}$			
DRAWN BY	MLD	MAT'L:	SCALE NONE
DATE	5-21-88	SEE TABLE	DRAWING NO.
CHK'D			GB1932BL
			CDS A SIZE

2	4/28/03	JAD		COMPLETELY REVISED, REMOVED GERMAN TEXT	GB1932BL	2			
REV	DATE	BY	CHK	DESCRIPTION	ECN - R	CUST	SUP		