

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Draw ings
 - PDF-Service Post ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove)Search Tips Within Results

 **Text Search: 'SPF2-2/0-Q'**

Your search criteria matched only one product, shown below

SPF2-2/0-Q



Female - Two Cables

- For grounding two copper code conductors to steel structures, busbars, or transformers or for tapping from busbar using external threaded studs, screws, or bolts
- Made from high copper content, hard drawn copper rod provides high strength
- Wide wire range-taking capability minimizes inventory requirements
- True hex design for body and nut hex provides correct fit with socket, box, or open end wrenches resulting in proper torquing of electrical connection
- Pressure bar provides secure connection on a full range of conductor combinations used with each connector providing premium wire pull-out strength
- UL Listed for grounding and bonding and suitable for direct burial in earth or concrete

Part Number	SPF2-2/0-Q
RoHS Compliancy Status	Compliant
Part Description	Bronze, service post connector, female, tw o cables, type SPF2.
Product Type	Grounding Connectors - Service Post
UL Listed	Yes
Length (In.)	2.31
Length (mm)	58.7
Copper Conductor Size Range	#2 SOL – 2/0 STR
Body Hex	.88
Nut Hex	1.13
Pricing Description	Bronze Service Post Connector, #2 SOL-2/0 STR, female, 2 cables
Stud Length (In.)	.50
Stud Length (mm)	12.7
Thread size	1/2 – 13
Tightening Torque (In-Lbs)	500
Wire Diameter Range (In.)	.258-.419
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.