



Network and Electrical Solutions
UNIFIED PHYSICAL INFRASTRUCTURESM



- Home
- Industries
- Solutions
- Products
- Partners
- Support
- About Us
- Careers

Entire Site

Search Results

- Evaluate
- FAQ's
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips ☐ Within Results

Text Search: 'TV105-1MY'

Your search criteria matched only one product, shown below

TV105-1MY



- Non-Shrink oil resistant flexible clear tubing on reel
- Provides insulation and protection for lead wires wire harness assemblies soldered joints & components in electrical and electronic equipment
 - Material: Polyvinyl chloride (PVC)
 - Voltage Rating: 300V and 600V
 - All purpose flexible non-shrinkable
 - Resistant to heat and moisture
- Applicable Specifications:
- UL224 VW-1
 - CSA C22.2 No. 198.1 (OFT)
 - ASTM D-922 Grade CFR
 - MIL-I-631 Type F, Form U, Grade C- Class 1 Category 1

▪ Part Number	TV105-1MY
▪ RoHS Compliancy Status	Compliant
▪ Note	TV105-1MY replaces TV105-1TLY
▪ Part Description	PVC Non-Shrink Tubing, 105°C rated
▪ Material	Polyvinyl Chloride
▪ Color	Clear
▪ CSA Certified	Yes

▪ CSA Specification	CSA C22.2 No. 198.1 (OFT)
▪ UL Recognized	E122770
▪ UL Recognized Specification	UL224 VW-1
▪ Flammability Rating	UL224 VW-1
▪ Length Per Reel (ft.)	1000
▪ Length Per Reel (m)	304.8
▪ Max. Inside Diameter (In.)	.311
▪ Max. Inside Diameter (mm)	7.89
▪ Max. Voltage Rating	300 V
▪ Min. Inside Diameter (mm)	7.34
▪ Minimum Inside Diameter (In.)	.289
▪ Nominal Size	1 AWG
▪ Pricing Description	Vinyl Tubing, 1 AWG (8.81mm), 300V, Clear
▪ Temperature Range	-4°F to 221°F (-20°C to 105°C)
▪ Wall Thickness (In.)	.020
▪ Wall Thickness (mm)	.51
▪ Min. Order UOM	RL
▪ Min. Order Qty.	1
▪ BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
▪ Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.