



Search Results

- Evaluate
- FAQ's
- Design a Solution
- Part Drawings
- PDFNon-Shrink P ..
- How to Buy
- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click to remove) Search Tips Within Results

Text Search: 'TV105-.50DY'

Your search criteria matched only one product, shown below

TV105-.50DY



- Non-Shrink oil resistant flexible clear tubing on reel
- Provides insulation and protection for lead wires wire harness assemblies soldered joints and components in electrical and electronic equipment
 - Material: Polyvinyl chloride (PVC)
 - Voltage Rating: 300V and 600V
 - All purpose flexible non -shrinkable
 - Resistant to heat and moisture
- Applicable Specifications:
- UL224 VW-1
 - CSA C22.2 No. 198.1 (OFT)
 - ASTM D-922 Grade CFR
 - MIL-I-631 Type F, Form U, Grade C- Class 1 Category 1

Part Number	TV105-.50DY
RoHS Compliance Status	Compliant
Note	TV105-.50DY replaces TV105-.50TL
Part Description	PVC NonShrink Tubing, 105°C rated
Material	Polyvinyl Chloride
Color	Clear
CSA Certified	Yes
CSA Specification	CSA C22.2 No. 198.1 (OFT)
UL Recognized	E122770
UL Recognized Specification	UL224 VW-1
Flammability Rating	UL224 VW-1
Length Per Reel (ft.)	500
Length Per Reel (m)	152.4
Max. Inside Diameter (In.)	.524
Max. Inside Diameter (mm)	13.30
Max. Voltage Rating	600 V
Min. Inside Diameter (mm)	12.70
Minimum Inside Diameter (In.)	.500
Nominal Size	1/2
Pricing Description	Vinyl Tubing, .50" (12.7mm), 600V, Clear
Temperature Range	-4°F to 221°F (20°C to 105°C)
Wall Thickness (In.)	.025
Wall Thickness (mm)	.64
Min. Order UOM	RL
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	0
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.