

UTPK6A10BL

 Include all of the same features as the TX6A[™] 10Gig[™] UTP Patch Cords with the added benefit of visual and mechanical security Mechanical keyed configurations prevent unintentional insertion into adjacent ports (6) versions) Color-coded for easy identification Exceed ANSI/TIA-568-C.2, ISO 11801 Class E_A Edition 2.1 and IEEE 802.3an-2006 channel requirements for supporting 10GBASE-T Meet requirements of IEEE 802.3af and IEEE 802.3at for PoE applications Each patch cord is 100% performance tested and wired T568B Constructed of TX6A[™] 10Gig[™] 23 AWG stranded UTP copper cable (nominal cable diameter) is .275 inches) and TX6™ PLUS Modular Plugs for superior performance Plug meets all applicable ANSI/TIA-968-A requirements and exceeds IEC 60603-7 specifications

Slender strain relief boot provides easy access in high density applications

 Plug uses an integral pair manager to optimize performance and consistency by reducing untwisting of conductors within the plug

 Plug performance in center of TIA/EIA component range, ensuring interoperability and 10GBASE-T Ethernet channel. performance

- Labels on patch cords provide identification of performance level, length, and quality control number
- Patented tangle free latch prevents snags and provides easy release, saving time on frequent moves, adds, and changes
- Optional Patch Cord Color Bands snap on and off individual patch cords offering endless color-coding options

Part Number	UTPK6A10BL
 RoHS Compliancy Status 	Compliant
 Part Description 	Keyed, Category 6A, 10Gb/s UTP patch cord with TX6™ PLUS Keyed Modular Plug on one end and TX6™ PLUS Non-Keyed Modular Plug on the other end.
 Product Type 	Keyed Copper Patch Cord
Color	Black
 Length (ft.) 	10

 Length (m) 	3.05
Cable Color	Black
 Cable Type 	UTP
CE Compliant	No
 Connector 1 Type 	RJ45 8(8)
 Connector 2 Type 	RJ45 8(8)
 Flammability Rating 	CM
 Performance Level 	Category 6A/Class EA
 Pricing Description 	Keyed Copper Patch Cord, Cat 6A, Black UTP Cable, 10 Feet
 Termination End 1 	Keyed Modular Plug
 Termination End 2 	Non-Keyed Modular Plug
 Wiring Scheme 	T568B
 Min. Order UOM 	PC
 Min. Order Qty. 	1
 BOM Gty. (# of Pkgs.) 	0

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Home | Industries | Solutions | Services | Products | Partners | Support | Contact Us | Site Map | Careers Copyright @1995-2012, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy