



THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



NOTES:

1. DIMENSIONS IN BRACKETS [] ARE METRIC [mm].
2. PRODUCT DESIGNED AS OPTIONAL METHOD TO CONNECT ADJOINING QB-TILES.
3. PRODUCT IS RATED FOR ENVIRONMENTAL CONDITIONS OF 40-100°F IN ALL HUMIDITY RANGES.
4. PRODUCT IS 20% GF NYLON WITH ALUMINUM INSERTS
5. COMPATIBLE WITH FLATHEAD PHILLIPS DRIVE #10-32 X 1-1/4" SCREWS (INCLUDED).




SCALE 1:2

00	07-01-15	ANF	DJW	MSAD	DRAWING RELEASED				GAECN03015
REV	DATE	BY	CHK	APR	DESCRIPTION				ECN

<p>TITLE</p> <p>QUICK-BUILD GRID CONNECTOR; OPTIONAL TO SECURE TILES; 5 PER PACKAGE (QB-CONN)</p> <p>CUSTOMER DRAWING</p>									
ITEM REVISION NAME					14L203AU/01				
DATASET FILE NAME					14L203AU-DC				
<p>UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]</p> <p>.x ± .1 [2.54] .xxx ± .005 [.127]</p> <p>.xx ± .01 [.25] ANGLES ± 5 °</p>									
DRAWING NUMBER:					14L203AU-DC				
DRAWN BY		DATE		CHK		SCALE		SIZE	
ANF		07-01-15		DJW		1:1		SHT 1 OF 1	



SEE NOTES



THIRD ANGLE PROJECTION