

## Label, highly flexible - MM-EMLF (EX10)R C1 GN/WH - 0803950

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Highly flexible label, continuous, cassette, green with white imprint, mounting type: adhesive, can be marked with THERMOFOX

RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 055626 212289 |
| GTIN         | 4055626212289                                                                                           |

### Technical data

#### Dimensions

|            |         |
|------------|---------|
| Length (b) | 8000 mm |
| Width (a)  | 10 mm   |

#### Ambient conditions

|                                 |                                                                               |
|---------------------------------|-------------------------------------------------------------------------------|
| Ambient temperature (operation) | -20 °C ... 75 °C                                                              |
| Recommended storage conditions  | 20°C/50% relative humidity. Storage in the original packaging is recommended. |

#### General

|                                                                     |                                |
|---------------------------------------------------------------------|--------------------------------|
| Color                                                               | green                          |
| Components                                                          | Free from silicone and cadmium |
| Material                                                            | Vinyl polymer                  |
| RoHS compliant                                                      | Yes                            |
| Wipe resistance                                                     | DIN EN 61010-1 (VDE 0411-1)    |
| Adhesive                                                            | Acrylic                        |
| Printability                                                        | Thermal transfer               |
| Device                                                              | 0803984 THERMOFOX              |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02           |
| Result                                                              | Test passed                    |

## Label, highly flexible - MM-EMLF (EX10)R C1 GN/WH - 0803950

### Technical data

#### General

|                                                    |                                     |
|----------------------------------------------------|-------------------------------------|
| Test specification weathering-resistance           | Following ISO 4892-2:2013-03        |
| Test duration                                      | 96 h                                |
| Result of weather resistance test                  | Test passed                         |
| Salt spray test specification                      | DIN EN 60068-2-11:2000-02           |
| Test duration                                      | 96 h                                |
| Salt spray testing result                          | Test passed                         |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result of wipe resistance test                     | Test passed                         |
| Marking mounting type                              | adhesive                            |

#### Standards and Regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27400629 |
| eCl@ss 4.0    | 24190200 |
| eCl@ss 4.1    | 24190200 |
| eCl@ss 5.0    | 27149100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27149100 |
| eCl@ss 7.0    | 27149129 |
| eCl@ss 8.0    | 27149129 |
| eCl@ss 9.0    | 27400629 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000761 |
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |
| ETIM 6.0 | EC001288 |
| ETIM 7.0 | EC001288 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |

## Label, highly flexible - MM-EMLF (EX10)R C1 GN/WH - 0803950

### Classifications

#### UNSPSC

|              |          |
|--------------|----------|
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2  | 39131504 |
| UNSPSC 18.0  | 39131504 |
| UNSPSC 19.0  | 39131504 |
| UNSPSC 20.0  | 39131504 |
| UNSPSC 21.0  | 39131504 |

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>