

Zack Marker strip, flat - ZBF 12 CUS - 0825018

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 12 mm, lettering field size: 5.15 x 12.15 mm

The figure shows the 15 mm wide version

Why buy this product

- The ZBF zack marker strip system with flat marker groove is a marking solution for modular terminal blocks and electronics modules
- Sealing caps with external or inner thread
- Printed or unprinted marking labels
- ☑ Labeling service: Phoenix Contact can custom-label all zack marker strip markers according to your requirements.



Key Commercial Data

Packing unit	1 STK
GTIN	4 046356 357555
GTIN	4046356357555

Technical data

Dimensions

Width (a)	12 mm

Ambient conditions

Ambient temperature (operation)	-40 °C 100 °C
---------------------------------	---------------

General

Color	white
Туре	flat
Components	free from silicone and halogen
Flammability rating according to UL 94	V2
Material	PA
Wipe resistance	DIN EN 61010-1 (VDE 0411-1)



Zack Marker strip, flat - ZBF 12 CUS - 0825018

Technical data

General

Number of individual labels	5
Number of individual labels per row	5
Number of marker strips	5
Marking mounting type	snap into flat marker groove

Standards and Regulations


Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
Flammability rating according to UL 94	V2

Environmental Product Compliance

China RoHS	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
------------	---

Drawings

Schematic diagram



- ① Horizontal
- ② Vertical

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com