

Conductor marker - UC-WMC 1,9 (15X4) RD - 0828006

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Conductor marker, Sheet, red, unlabeled, can be labeled with: BLUEMARK CLED, BLUEMARK LED, Plotter, Mounting type: clip on, Cable diameter: 1.2-1.9 mm, Lettering field: 15 x 4 mm



Product Features

- The UC-WMC ... UniCard labeling range includes markers for captive labeling of control lines to cable sheaths with large diameters
- One-handed assembly
- Can be clipped on even after wiring has been completed
- Two labeling areas that are clearly legible at all times
- Labeling service: Phoenix Contact can custom-label all UniCard markers according to your requirements
- The markers, which are supplied in uniform sheets, can be labeled quickly and easily using the BLUEMARK LED
- The sheets provide space for including function texts
- The format automatically ensures printing with a high degree of positioning accuracy
- The markers support multi-line labeling

Key Commercial Data

| Packing unit | 1 pc |
|--------------------------------------|--------|
| Minimum order quantity | 10 pc |
| Weight per Piece (excluding packing) | 12.0 g |
| Country of origin | Poland |

Technical data

Dimensions

| Width (a) | 15 mm |
|----------------|---------------|
| Cable diameter | 1.2 mm 1.9 mm |

Ambient conditions

| | Ambient temperature (operation) | -40 °C 120 °C |
|--|---------------------------------|---------------|
|--|---------------------------------|---------------|

General

| Color | red |
|------------|--------------------------------|
| Components | free from silicone and halogen |



Conductor marker - UC-WMC 1,9 (15X4) RD - 0828006

Technical data

General

| Flammability rating according to UL 94 | V2 |
|--|-----------------------------|
| Material | PA |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 20 |
| Number of individual labels per row | 4 |
| Marking mounting type | clip on |

Standards and Regulations

| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|--|-----------------------------|
| Flammability rating according to UL 94 | V2 |

Classifications

eCl@ss

| eCl@ss 4.0 | 24190219 |
|------------|----------|
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27149103 |
| eCl@ss 5.1 | 27400401 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 7.0 | 27400401 |
| eCl@ss 8.0 | 27149129 |
| eCl@ss 9.0 | 27400629 |

ETIM

| ETIM 2.0 | EC000761 |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |

UNSPSC

| UNSPSC 6.01 | 30211811 |
|---------------|----------|
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11 | 39121410 |
| UNSPSC 12.01 | 39121410 |
| UNSPSC 13.2 | 39121410 |

Accessories

Accessories



Conductor marker - UC-WMC 1,9 (15X4) RD - 0828006

Accessories

Magazine

Magazine - P1 UC-MAG 1 - 5146079



Magazine, for CMS-P1-PLOTTER, for accommodating UC-TM..., UC-TMN..., UC-WMC 3,1..., UC-WMTBA...

Phoenix Contact 2016 $\ensuremath{\mathbb{C}}$ - all rights reserved http://www.phoenixcontact.com

05/23/2016 Page 3 / 3