

Accessories - PTCM-MP-PI 0,34-0,75 - 1013989


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Crimp contact, type of contact: Male connector, connection method: Crimp connection, contact surface: Tin



Key Commercial Data

Packing unit	100 pc
Minimum order quantity	100 pc
GTIN	 4 055626 492957
GTIN	4055626492957

Technical data

General

Range of articles	PTCM-MP-PI
-------------------	------------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 10.0.1	27440204
eCl@ss 4.0	27260700
eCl@ss 4.1	27260700
eCl@ss 5.0	27260700
eCl@ss 5.1	27260700
eCl@ss 6.0	27260700
eCl@ss 7.0	27440309
eCl@ss 8.0	27440204

Accessories - PTCM-MP-PI 0,34-0,75 - 1013989

Classifications

eCl@ss

eCl@ss 9.0	27440204
------------	----------

ETIM

ETIM 5.0	EC000796
ETIM 6.0	EC000796
ETIM 7.0	EC000796

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01687
-----	--	---------

Accessories

Accessories

Crimping tool

Crimping pliers - CRIMPFOX-P CC 0.75 L - 1064998



Crimping pliers, for COMBICON crimp connectors with cross section: 0.14 ... 0.75 mm². Unlockable pressure lock, precise parallel crimping, front entry, B crimp, incl. 2 positioning aids

Additional products

Printed-circuit board connector - PTCM 0,5/ 2-PI-2,5 WH - 1015242



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 2, pitch: 2.5 mm, connection method: Crimp connection, color: white, contact surface: Tin

Accessories - PTCM-MP-PI 0,34-0,75 - 1013989

Accessories

Printed-circuit board connector - PTCM 0,5/ 3-PI-2,5 WH - 1015243



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 3, pitch: 2.5 mm, connection method: Crimp connection, color: white, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 4-PI-2,5 WH - 1015244



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 4, pitch: 2.5 mm, connection method: Crimp connection, color: white, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 5-PI-2,5 WH - 1015245



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 5, pitch: 2.5 mm, connection method: Crimp connection, color: white, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 6-PI-2,5 WH - 1015246



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 6, pitch: 2.5 mm, connection method: Crimp connection, color: white, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 7-PI-2,5 WH - 1015247



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 7, pitch: 2.5 mm, connection method: Crimp connection, color: white, contact surface: Tin

Accessories - PTCM-MP-PI 0,34-0,75 - 1013989

Accessories

Printed-circuit board connector - PTCM 0,5/ 8-PI-2,5 WH - 1015248



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 8, pitch: 2.5 mm, connection method: Crimp connection, color: white, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 2-PI-2,5 BK - 1047894



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 2, pitch: 2.5 mm, connection method: Crimp connection, color: black, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 3-PI-2,5 BK - 1047897



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 3, pitch: 2.5 mm, connection method: Crimp connection, color: black, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 4-PI-2,5 BK - 1047898



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 4, pitch: 2.5 mm, connection method: Crimp connection, color: black, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 5-PI-2,5 BK - 1047899



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 5, pitch: 2.5 mm, connection method: Crimp connection, color: black, contact surface: Tin

Accessories - PTCM-MP-PI 0,34-0,75 - 1013989

Accessories

Printed-circuit board connector - PTCM 0,5/ 6-PI-2,5 BK - 1047900



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 6, pitch: 2.5 mm, connection method: Crimp connection, color: black, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 7-PI-2,5 BK - 1047901



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 7, pitch: 2.5 mm, connection method: Crimp connection, color: black, contact surface: Tin

Printed-circuit board connector - PTCM 0,5/ 8-PI-2,5 BK - 1047902



PCB connector, nominal current: 6 A, rated voltage (III/2): 160 V, nominal cross section: 0.75 mm², number of positions: 8, pitch: 2.5 mm, connection method: Crimp connection, color: black, contact surface: Tin

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>