

## Sensor/Actuator cable - SAC-4P-5,0-600/M12FS FB - 1404012

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sensor/Actuator cable, 4-position, PP-EPDM halogen-free, Gray RAL 7035, free cable end, on Socket straight M12, A-coded, Cable length: 5 m, Hygienic design, with plastic knurl

### Why buy this product

- ✓ Easy and safe: 100% electrically tested plug-in components
- ✓ Easy to clean, thanks to the special hygienic design
- ✓ Contamination can be detected quickly – thanks to the light color



### Key Commercial Data

|                                      |   |
|--------------------------------------|---|
| Packing unit                         | 1 pc  |
| GTIN                                 | <br>4 046356 677585 |
| Weight per Piece (excluding packing) | 141.0 g   |
| Custom tariff number                 | 85444290  |
| Country of origin                    | Poland  |
| Note                                 | Made to Order (non-returnable)  |

### Technical data

#### Dimensions

|                 |     |
|-----------------|-----|
| Length of cable | 5 m |
|-----------------|-----|

#### Ambient conditions

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Ambient temperature (operation) | -40 °C ... 105 °C (Plug / socket) |
| Degree of protection            | IP65                              |
|                                 | IP67                              |
|                                 | IP68                              |
|                                 | IP69K                             |

#### General

|                       |       |
|-----------------------|-------|
| Rated current at 40°C | 4 A   |
| Rated voltage         | 250 V |
| Number of positions   | 4     |

# Sensor/Actuator cable - SAC-4P-5,0-600/M12FS FB - 1404012

## Technical data

### General

|                              |  |
|------------------------------|--|
| Contact resistance           | ≤ 5 mΩ                                   |
| Insulation resistance        | ≥ 100 MΩ                                 |
| Coding                       | A - standard                             |
| Standards/regulations        | M12 connector IEC 61076-2-101            |
|                              | Material conformance FDA 21 CFR 177.2600 |
| Status display               | No                                       |
| Protective circuit/component | Unwired                                  |
| Surge voltage category       | II                                       |
| Pollution degree             | 3  |
| Insertion/withdrawal cycles  | ≥ 100                                    |
| Torque                       | 0.4 Nm (M12 connector)                   |

### Material

|                          |               |
|--------------------------|---------------|
| Contact material         | CuSn          |
| Contact surface material | Ni/Au         |
| Contact carrier material | PP            |
| Material of grip body    | PP            |
| Material, knurls         | Polypropylene |
| Sealing material         | FKM           |

### Cable

|   |                                       |
|---|---------------------------------------|
| Cable type                                      | Halogen-free PP gray                  |
| Cable type (abbreviation)                       | 600                                   |
| Cable abbreviation                              | Li9Y9Y                                |
| Conductor cross section                         | 4x 0.34 mm <sup>2</sup> (signal line) |
| AWG signal line                                 | 22                                    |
| Conductor structure signal line                 | 42x 0.10 mm                           |
| Core diameter including insulation              | 1.27 mm ±0.02 mm (signal line)        |
| Thickness, insulation                           | ≥ 0.21 mm (Core insulation)           |
| Wire colors                                     | brown, white, blue, black             |
| Overall twist                                   | 4 wires, twisted                      |
| Length of twist, overall twist                  | 48 mm                                 |
| External sheath, color                          | Gray RAL 7035                         |
| Outer sheath thickness                          | approx. 0.8 mm                        |
| External cable diameter D                       | 4.7 mm ±0.15 mm                       |
| Minimum bending radius, fixed installation      | 5 x D                                 |
| Minimum bending radius, flexible installation   | 10 x D                                |
| Number of bending cycles                        | 4000000                               |
| Minimum bending radius, drag chain applications | 10 x D                                |
| Traversing path                                 | 10 m                                  |
| Traversing rate                                 | 3 m/s                                 |
| Acceleration                                    | 10 m/s <sup>2</sup>                   |

## Sensor/Actuator cable - SAC-4P-5,0-600/M12FS FB - 1404012

### Technical data

#### Cable

|                                 |   |
|---------------------------------|---|
| Cable weight                    | 30 kg/km  |
| Outer sheath, material          | PP-EPDM   |
| Material conductor insulation   | PP  |
| Conductor material              | Bare Cu litz wires  |
| Conductor resistance            | 58 $\Omega$ /km (at 20 °C)  |
| Nominal voltage, cable          | $\leq$ 300 V AC   |
| Test voltage, cable             | $\geq$ 3000 V AC (Spark test)   |
| Special properties              | FDA compliant according to FDA 21 CFR 177.2600                                    |
|                                 | highly flexible   |
|                                 | Flexible cable conduit capable  |
| Halogen-free                    | in accordance with DIN VDE 0472 part 815  |
| Other resistance                | Resistant to cold bending and cold impacts According to DIN EN 60811-1-4 (-40 °C) |
| Ambient temperature (operation) | -40 °C ... 105 °C (cable, fixed installation)                                     |
|                                 | -25 °C ... 105 °C (cable, flexible installation)                                  |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060306 |
| eCl@ss 4.1 | 27060306 |
| eCl@ss 5.0 | 27061801 |
| eCl@ss 5.1 | 27061801 |
| eCl@ss 6.0 | 27061801 |
| eCl@ss 7.0 | 27061801 |
| eCl@ss 8.0 | 27279218 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC001855 |
| ETIM 4.0 | EC001855 |
| ETIM 5.0 | EC001855 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |

### Approvals

#### Approvals

## Sensor/Actuator cable - SAC-4P-5,0-600/M12FS FB - 1404012

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

Approvals submitted

---

### Approval details

|     |
|-----|
| EAC |
|-----|

### Accessories

Accessories

Cutting tools

Diagonal cutter - CUTFOX-S VDE - 1212207



Diagonal cutter for copper and aluminum conductors, VDE 1000 V AC/ 1500 V DC-tested

---

### Stripping tool

Stripping tool - WIREFOX SAC - 1212623



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

---

Stripping tool - WIREFOX 10 - 1212150




Stripping tool, for cables and conductors from 0.02 - 10 mm<sup>2</sup>, self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm<sup>2</sup> stranded/1.5 mm<sup>2</sup> solid, replaceable stripping blade

---

## Sensor/Actuator cable - SAC-4P-5,0-600/M12FS FB - 1404012


### Drawings

Schematic diagram




Pin assignment M12 socket, 4-pos., A-coded, view female side

Cable cross section




Halogen-free PP gray [600]

Dimensional drawing



M12 x 1 socket, straight

Circuit diagram



Contact assignment of the M12 socket