

## Network cable - VS-IP67-IP67-94C-LI/10,0 - 1413146

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled Ethernet cable, shielded, 4-pair, AWG 26 flexible cable conduit capable (19-wire), RAL 5021 (sea blue), RJ45 connector/IP67 gray to RJ45 connector/IP67, gray, line, length 10 m

RoHS IP67

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 046356 475761 |
| GTIN         | 4046356475761                                                                                           |

### Technical data

#### Dimensions

|                 |         |
|-----------------|---------|
| Length of cable | 10.00 m |
|-----------------|---------|

#### Ambient conditions

|                      |      |
|----------------------|------|
| Degree of protection | IP67 |
|----------------------|------|

#### General data

|                                       |                |
|---------------------------------------|----------------|
| Number of positions                   | 8              |
| Overvoltage category                  | I              |
| Degree of pollution                   | 2              |
| Alternative short product description | Ethernet cable |
| Locking type                          | Push Pull      |
| Degree of protection                  | IP67           |
| Number of slots                       | 1              |

#### Characteristics head 1

|                        |     |
|------------------------|-----|
| Shielded               | yes |
| Outer sheath, material | PUR |

#### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V2 |
|----------------------------------------|----|

# Network cable - VS-IP67-IP67-94C-LI/10,0 - 1413146

## Technical data

### Cable

|                                                      |                                                                            |
|------------------------------------------------------|----------------------------------------------------------------------------|
| Cable type                                           | Ethernet drag chain CAT5, 4-pair                                           |
| Cable type (abbreviation)                            | 94C                                                                        |
| UL AWM style                                         | 20963 (80°C/30 V)                                                          |
| Cable structure                                      | 4x2xAWG26/19; S/UTP                                                        |
| Conductor cross section                              | 4x 2x 0.14 mm <sup>2</sup>                                                 |
| AWG signal line                                      | 26                                                                         |
| Conductor structure signal line                      | 19x 0.10 mm                                                                |
| Core diameter including insulation                   | 1 mm                                                                       |
| Wire colors                                          | white/blue-blue, white/orange-orange, white/green-green, white/brown-brown |
| Twisted pairs                                        | 2 cores to the pair                                                        |
| Overall twist                                        | Four pairs and four fillers to the core                                    |
| Shielding                                            | Tinned copper braided shield                                               |
| Optical shield covering                              | 90 %                                                                       |
| External sheath, color                               | water blue RAL 5021                                                        |
| Outer sheath thickness                               | 0.85 mm                                                                    |
| External cable diameter D                            | 6.9 mm +0.1 mm ... 0.2 mm                                                  |
| Minimum bending radius, fixed installation           | 4 x D                                                                      |
| Minimum bending radius, flexible installation        | 8 x D                                                                      |
| Number of bending cycles                             | 5000000                                                                    |
| Minimum bending radius, drag chain applications      | 7,5 x D                                                                    |
| Traversing rate                                      | 3 m/s                                                                      |
| Acceleration                                         | 5 m/s <sup>2</sup>                                                         |
| Tensile strength GRP                                 | ≤ 100 N                                                                    |
| Cable weight                                         | 57 kg/km                                                                   |
| Outer sheath, material                               | PUR                                                                        |
| Material conductor insulation                        | PP                                                                         |
| Conductor material                                   | Bare Cu litz wires                                                         |
| Insulation resistance                                | ≥ 500 MΩ*km                                                                |
| Loop resistance                                      | ≤ 290.00 Ω/km                                                              |
| Cable capacity                                       | approx. 50 nF/km (at 1 kHz)                                                |
| Wave impedance                                       | 100 Ω ±5 Ω (at 100 MHz)                                                    |
| Near end crosstalk attenuation (NEXT)                | 65.3 dB (with 1 MHz)                                                       |
|                                                      | 56.3 dB (at 4 MHz)                                                         |
|                                                      | 50.3 dB (at 10 MHz)                                                        |
|                                                      | 47.2 dB (at 16 MHz)                                                        |
|                                                      | 45.8 dB (at 20 MHz)                                                        |
|                                                      | 42.9 dB (at 31.25 MHz)                                                     |
|                                                      | 38.4 dB (at 62.5 MHz)                                                      |
|                                                      | 35.3 dB (at 100 MHz)                                                       |
| Power-summed near end crosstalk attenuation (PSNEXT) | 62.3 dB (with 1 MHz)                                                       |

# Network cable - VS-IP67-IP67-94C-LI/10,0 - 1413146

## Technical data

### Cable

|                                         |                                                 |
|-----------------------------------------|-------------------------------------------------|
|                                         | 53.3 dB (at 4 MHz)                              |
|                                         | 47.3 dB (at 10 MHz)                             |
|                                         | 44.2 dB (at 16 MHz)                             |
|                                         | 42.8 dB (at 20 MHz)                             |
|                                         | 39.9 dB (at 31.25 MHz)                          |
|                                         | 35.4 dB (at 62.5 MHz)                           |
|                                         | 32.3 dB (at 100 MHz)                            |
| Attenuation                             | 3.2 dB (with 1 MHz)                             |
|                                         | 6 dB (at 4 MHz)                                 |
|                                         | 9.5 dB (at 10 MHz)                              |
|                                         | 12.1 dB (at 16 MHz)                             |
|                                         | 13.6 dB (at 20 MHz)                             |
|                                         | 17.1 dB (at 31.25 MHz)                          |
|                                         | 24.8 dB (at 62.5 MHz)                           |
|                                         | 32 dB (at 100 MHz)                              |
| Return loss (RL)                        | 23 dB (at 4 MHz)                                |
|                                         | 24.1 dB (at 8 MHz)                              |
|                                         | 25 dB (at 10 MHz)                               |
|                                         | 25 dB (at 16 MHz)                               |
|                                         | 25 dB (at 20 MHz)                               |
|                                         | 23.6 dB (at 31.25 MHz)                          |
|                                         | 21.5 dB (at 62.5 MHz)                           |
|                                         | 20.1 dB (at 100 MHz)                            |
| Signal runtime                          | 5.3 ns/m                                        |
| Coupling resistance                     | ≤ 100.00 mΩ/m (at 10 MHz)                       |
| Nominal voltage, cable                  | ≤ 100 V                                         |
| Test voltage Core/Core                  | 700 V (50 Hz, 1 min.)                           |
| Test voltage Core/Shield                | 700 V (50 Hz, 1 min.)                           |
| Flame resistance                        | according to IEC 60332-1-2                      |
| Halogen-free                            | according to IEC 60754-1                        |
| Resistance to oil                       | according to EN 60811-2-1                       |
| Ambient temperature (operation)         | -40 °C ... 80 °C (cable, fixed installation)    |
|                                         | -20 °C ... 80 °C (cable, flexible installation) |
| Ambient temperature (installation)      | -20 °C ... 80 °C                                |
| Ambient temperature (storage/transport) | -20 °C ... 80 °C                                |


### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |


## Drawings

## Network cable - VS-IP67-IP67-94C-LI/10,0 - 1413146

Dimensional drawing



Circuit diagram



## Network cable - VS-IP67-IP67-94C-LI/10,0 - 1413146

Cable cross section



Ethernet drag chain CAT5, 4-pair [94C]

### Classifications

eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27060308 |
| eCl@ss 4.0    | 24010400 |
| eCl@ss 4.1    | 24010400 |
| eCl@ss 5.0    | 19030300 |
| eCl@ss 5.1    | 19030300 |
| eCl@ss 6.0    | 27061800 |
| eCl@ss 7.0    | 27060308 |
| eCl@ss 8.0    | 27060308 |
| eCl@ss 9.0    | 27060308 |

## Network cable - VS-IP67-IP67-94C-LI/10,0 - 1413146

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000830 |
| ETIM 4.0 | EC002599 |
| ETIM 5.0 | EC002599 |
| ETIM 6.0 | EC001262 |
| ETIM 7.0 | EC001262 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 26121616 |
| UNSPSC 7.0901 | 26121616 |
| UNSPSC 11     | 26121604 |
| UNSPSC 12.01  | 31261501 |
| UNSPSC 13.2   | 26121604 |
| UNSPSC 18.0   | 26121604 |
| UNSPSC 19.0   | 26121604 |
| UNSPSC 20.0   | 26121604 |
| UNSPSC 21.0   | 26121604 |

### Approvals

#### Approvals

#### Approvals

#### EAC

#### Ex Approvals

#### Approval details

|     |                                                                                     |          |
|-----|-------------------------------------------------------------------------------------|----------|
| EAC |  | 19060508 |
|-----|-------------------------------------------------------------------------------------|----------|