

## Housing - HC-EVO-B24-SHWS-2SSM32-PLRBK - 1421367

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Box mounting bases B24, with single locking latch, material: PA, cable outlets: 2, lateral, height: 84 mm, cable gland: none, support sleeve: no, 2x M32, Standard, including 2x reducing adapter

### Your advantages

- ✓ Lower costs than metal version
- ✓ Low weight
- ✓ Lower risk of condensation
- ✓ Both contact insert PE sheets are connected by means of a metal frame integrated in the sleeve housing
- ✓ Metal inlays ensure leading PE contact with angled plugs
- ✓ Completely corrosion-resistant
- ✓ Halogen-free plastic
- ✓ Marking label can be attached



### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 1 pc                                                                                                    |
| GTIN         | <br>4 055626 264943 |
| GTIN         | 4055626264943                                                                                           |

### Technical data

#### Dimensions

|        |        |
|--------|--------|
| Height | 84 mm  |
| Width  | 57 mm  |
| Length | 144 mm |

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Degree of protection (IP)       | IP66              |
| Degree of protection (NEMA)     | 12 (UL 50e)       |
| Ambient temperature (operation) | -40 °C ... 125 °C |

#### General

## Housing - HC-EVO-B24-SHWS-2SSM32-PLRBK - 1421367

### Technical data

#### General

|                                        |                                                                                                         |
|----------------------------------------|---------------------------------------------------------------------------------------------------------|
| Note                                   | For contact inserts HC-B24, BB46, D64, DD108, M, K, HV10-I-PT, HV 10-E...C                              |
| Size                                   | B24                                                                                                     |
| Housing type                           | Box mounting bases                                                                                      |
| Color                                  | black                                                                                                   |
| Locking type                           | with single locking latch                                                                               |
| No. of cable outlets                   | 2                                                                                                       |
| Cable outlet                           | lateral                                                                                                 |
| Screw connection                       | none                                                                                                    |
| Type of the screw connection           | 2x M32                                                                                                  |
| Housing material                       | PA                                                                                                      |
| Seal material                          | NBR                                                                                                     |
| Material lock                          | PA                                                                                                      |
| Flammability rating according to UL 94 | V0                                                                                                      |
| Assembly instructions                  | Two plastic reductions M40 to M32 are provided                                                          |
| Connection                             | One of the two openings for the screw connections is sealed but can be broken open using a screwdriver. |

#### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|


#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Drawings

## Housing - HC-EVO-B24-SHWS-2SSM32-PLRBK - 1421367

Dimensional drawing



Dimensional drawing

### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27440202 |
| eCl@ss 5.1    | 27261200 |
| eCl@ss 6.0    | 27261200 |
| eCl@ss 7.0    | 27440202 |
| eCl@ss 8.0    | 27440202 |
| eCl@ss 9.0    | 27440202 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC000437 |
| ETIM 6.0 | EC000437 |
| ETIM 7.0 | EC000437 |

#### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 13.2 | 31261501 |
| UNSPSC 18.0 | 31261501 |
| UNSPSC 19.0 | 31261501 |
| UNSPSC 20.0 | 31261501 |
| UNSPSC 21.0 | 31261501 |

### Approvals

#### Approvals

## Housing - HC-EVO-B24-SHWS-2SSM32-PLRBK - 1421367

### Approvals

Approvals

EAC / DNV GL

---

Ex Approvals

---

### Approval details

|        |                                                                                   |                                                                                   |            |
|--------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------|
| EAC    |  | RU C-<br>DE.AI30.B.01102                                                          |            |
| DNV GL |  | <a href="https://approvalfinder.dnvgl.com/">https://approvalfinder.dnvgl.com/</a> | TAE000037S |

### Accessories

Accessories

Device marking

Snap-in markers - US-EMP (20X9) - 0829439



Snap-in markers, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped into marker carrier, lettering field size: 20 x 9 mm, Number of individual labels: 70

### Full screw connection

Cable gland - G-INS-M32-M68N-PNES-BK - 1411136



Cable gland, cable gland material: PA, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: jet black RAL 9005

### Housing latches

## Housing - HC-EVO-B24-SHWS-2SSM32-PLRBK - 1421367

### Accessories

Single locking latch - HC-B24-SL-PLBK - 1407701



Replacement single locking latch for HEAVYCON EVO housing type B24, PA

---

### Protective cover

Protective covers - HC-B24-BC-HI-PLBK - 1407695



HEAVYCON EVO hinged protective cover, size B24, for EVO plastic supporting base element, IP65, PA

---

Protective covers - HC-B24-BCSFS-P-BK - 1414627



Protective cover B24, for single locking latch, protective cover material: PA, height: 18.5 mm, seal: no, diameter of retaining cord eyelet: 40 mm

---

### Seal

Profile gasket - HC-B24-SP-RBK - 1407709



Profile gasket for HEAVYCON EVO supporting base element type B24

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>