

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

HEAVYCON D7 box mounting base, with single locking latch, height 25.5 mm, with 1 x Pg11 screw connection, with open bottom, zinc





## Key commercial data

Packing unit	1 pc
GTIN	4 017918 036966
Weight per Piece (excluding packing)	30.22 GRM
Custom tariff number	85472000
Country of origin	Germany

#### Technical data

#### **Dimensions**

Height	25.5 mm
Width	40.5 mm
Length	38 mm
Wrench size, union nut	18 mm
External cable diameter	7.5 mm 12.5 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP54
	IP65 (with sealing screw)
Ambient temperature (operation)	-40 °C 125 °C

#### General

Note	For contact inserts HC-D7, D8, A3, A4, B5, HS2-D7
Design	D7



## Technical data

#### General

Housing type	Box mounting bases
Locking type	With single locking latch
No. of cable exits	1
Cable exit	Lateral
Screw connection	With
Type of the screw connection	1x Pg11
Housing material	Polyamide
Housing surface material	PA, light gray
Seal material	NBR
Cable gland material	Polyamide
Cable seal material	NBR
Material lock	Polyamide

## Classifications

## eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

#### **ETIM**

ETIM 2.0	EC000437
ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502




Approvals
approvals
pprovals
OST
x Approvals
pprovals submitted
approval details
GOST C
Accessories
accessories
flounting material
sealing screw - HC-D 7-DS-IP65 - 1686229
Sealing screw, for IP65 protection

Drawings



#### Dimensioned drawing



© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com