

Electronic housing - HCS-T MAXI 1W C C C 7035 - 2203142

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Handheld housing, T-Maxi, light gray, consisting of two half shells with screws, front 1.1 mm recessed, with window and keypad slot

Your advantages

- ✓ Item is from the HCS product range
- ✓ Suitable for handheld devices
- ✓ Ergonomic straight or staggered housing design
- ✓ Integration of LCD displays and membrane keypads
- ✓ Degree of protection: up to IP54
- ✓ Temperature range: -20 °C to +50 °C
- ✓ Shock-resistant ABS plastic
- ✓ Flammability rating UL 94-V0

RoHS

IP54

Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 376943
GTIN	4055626376943

Technical data

Item properties

Type	HCS-T MAXI 1W C C C 7035
Order No.	2203142
Housing type	Handheld housing
Type	stepped
Max. IP code to attain	IP54
Battery compartment	no

Measurements

Electronic housing - HCS-T MAXI 1W C C C 7035 - 2203142

Technical data

Measurements

Caption	Schematic representation – for additional information, see product range drawing in the Download Center
Width [w]	116 mm
Height [h]	253 mm
Depth [d]	46 mm

Material specifications

Color (RAL)	light gray (7035)
Flammability rating according to UL 94	V0
Housing material	ABS

Hammer test

Specification	IEC 60068-2-75:2014-09
Impact energy	0.7 J
Number of drop cycles	5

Thermostability (ball thrust test)

Specification	IEC 60695-10-2:2014-02
Temperature	80 °C
Test duration	1 h
Force	20

Test for assessing the risk of fire (glow wire)

Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s

Packaging information

Pieces per package	1
Denomination packing units	Pcs.


Standards and regulations

Flammability rating according to UL 94	V0
--	----

Drawings

Electronic housing - HCS-T MAXI 1W C C C 7035 - 2203142

Dimensional drawing



Schematic representation – for additional information, see product range drawing in the Download Center

Classifications

eCl@ss

eCl@ss 10.0.1	27182702
eCl@ss 5.1	27180506
eCl@ss 6.0	27180800
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 5.0	EC001031
----------	----------

Electronic housing - HCS-T MAXI 1W C C C 7035 - 2203142

Classifications

ETIM

ETIM 6.0	EC001031
ETIM 7.0	EC001031

Accessories

Accessories

Screwdriver tools

Philips screwdriver - SF-PH 0-60 - 1212558



Screwdriver, PH crosshead, size: PH 0 x 60, 2-component grip, with non-slip grip

Additional products

Display - D L 4,6 128X P - 2203547



Graphic LCD module, 4.6", 128 x 128 pixels, FSTN transfective/positive 6:00, LED backlight, interface: parallel, operating temperature: -20 °C ... 70 °C

Washer/ring - HCS-T MAXI WIN 2,0 FR128X128 - 2203593



Acrylic glass, satin-finished, frame printed black, for display 128x64

Membrane keypad - KP HCS T-MAX K45 C4 P16 - 2203571



Membrane keypad, self-adhesive, silver conduction technology, 45 keys, embossed, 4 colors, connection cable: 77 mm, with crimp female connector RM 2.54 mm, operating temperature -20 °C ... 70 °C

Electronic housing - HCS-T MAXI 1W C C C 7035 - 2203142

Accessories

Seal - HCS-T MAXI SEAL - 2203582



Sealing set without battery chamber, including cord and O-rings

Mounting set - HCS-T MAXI D-FIX 4,6 SECND - 2203734



Mounting set including screws, for display on second PCB or display plate

Fixing plate - HCS-T MAXI DISPLAY PLATE - 2203866



Display plate for securing the display

Seal - HCS-T MAXI D-SEAL 4,6 - 2203741



Sealing frame, self-adhesive, lasered, for 4.6" display

Adhesive - HCS-T MAXI W-GLUE - 2203748



Transfer adhesive for display window

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>