

Electronic housing - ME 22,5 OT-3MSTBO GY S146 - 2695675

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

Upper part of housing, for COMBICON connection, three-level

Product Features

- ☑ ME...TBUS connector with 5 parallel contacts can be snapped onto DIN rails to save space
- Gold contacts for data transmission and power supply (125 V, 8 A)
- When a device is unplugged from the system as a whole, the signal chain is not interrupted# Supply via standard MINI COMBICON plug



Key commercial data

Packing unit	11
Minimum order quantity	250 1
Custom tariff number	85472000
Country of origin	Germany

Technical data

Product type	Component housing upper part
Approval	UL Recognized
Width	22.5 mm
Height	51.5 mm
Depth	105 mm
Color	gray (7042)
Number of connections	24
Connection method	Pluggable

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702



Electronic housing - ME 22,5 OT-3MSTBO GY S146 - 2695675

Classifications

eCl	ത	00
COI	w	ಶಾ


eCl@ss		
eCl@ss 8.0	27182702	
ETIM		
ETIM 2.0	EC001031	
ETIM 3.0	EC001031	
ETIM 4.0	EC000886	
ETIM 5.0	EC000886	
UNSPSC		
UNSPSC 6.01	31261501	
UNSPSC 7.0901	31261501	
UNSPSC 11	31261501	
UNSPSC 12.01	31261501	
UNSPSC 13.2	31261501	
Approvals Approvals		
UL Recognized		
Ex Approvals		
Approvals submitted		
Approval details		
UL Recognized 5		

Drawings



Electronic housing - ME 22,5 OT-3MSTBO GY S146 - 2695675

Dimensioned drawing



© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com