

## Filler plugs - ME MAX B-17,5 KMGY - 2706959

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



DIN rail housing, Filler plug for unoccupied terminal points, width: 15 mm, height: 21.6 mm, color: light gray (7035)

### Your advantages

- ✓ Easy, tool-free mounting
- ✓ Plastic in accordance with UL94 V0: for more rigorous flammability requirements

**RoHS** **IP20**

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 50 pc                                                                                                   |
| GTIN         | <br>4 017918 925260 |
| GTIN         | 4017918925260                                                                                           |

### Technical data

#### Item properties

|                              |                                            |
|------------------------------|--------------------------------------------|
| Brief article description    | Filler plugs                               |
| Type                         | ME MAX B-17,5 KMGY                         |
| Order No.                    | 2706959                                    |
| Housing type                 | DIN rail housing                           |
| Type                         | Filler plug for unoccupied terminal points |
| Max. IP code to attain       | IP20                                       |
| Mounting type                | Latching                                   |
| Ventilation openings present | no                                         |

#### Dimensions

|              |         |
|--------------|---------|
| Width [ w ]  | 15 mm   |
| Height [ h ] | 21.6 mm |

#### Material data

|             |                   |
|-------------|-------------------|
| Color (RAL) | light gray (7035) |
|-------------|-------------------|

# Filler plugs - ME MAX B-17,5 KMGY - 2706959

## Technical data

### Material data

|                                        |           |
|----------------------------------------|-----------|
| Flammability rating according to UL 94 | V0        |
| Housing material                       | Polyamide |

### Ambient conditions

|                                         |                                                    |
|-----------------------------------------|----------------------------------------------------|
| Ambient temperature (storage/transport) | -40 °C ... 55 °C                                   |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                   |
| Ambient temperature (operation)         | -40 °C ... 105 °C (depending on power dissipation) |
| Relative humidity (storage/transport)   | 80 %                                               |

### General information

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Type of note | Assembly instruction:                                       |
| Note         | Refer to the data sheet for the range in the download area. |

### Packaging information

|                            |                |
|----------------------------|----------------|
| Pieces per package         | 50             |
| Denomination packing units | Pcs.           |
| Outer packaging type       | Resealable bag |

### Standards and regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27182702 |
| eCl@ss 4.0    | 27180400 |
| eCl@ss 4.1    | 27180400 |
| eCl@ss 5.0    | 27180500 |
| eCl@ss 5.1    | 27180500 |
| eCl@ss 6.0    | 27180800 |
| eCl@ss 7.0    | 27182702 |
| eCl@ss 8.0    | 27182702 |
| eCl@ss 9.0    | 27182702 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC001031 |
| ETIM 3.0 | EC001031 |
| ETIM 4.0 | EC001031 |
| ETIM 5.0 | EC001031 |
| ETIM 6.0 | EC001031 |

## Filler plugs - ME MAX B-17,5 KMGY - 2706959

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 7.0 | EC001031 |
|----------|----------|

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 31261501 |
| UNSPSC 7.0901 | 31261501 |
| UNSPSC 11     | 31261501 |
| UNSPSC 12.01  | 31261501 |
| UNSPSC 13.2   | 31261501 |
| UNSPSC 18.0   | 31261501 |
| UNSPSC 19.0   | 31261501 |
| UNSPSC 20.0   | 31261501 |
| UNSPSC 21.0   | 31261501 |

### Approvals

#### Approvals

#### Approvals

UL Recognized / EAC

#### Ex Approvals

#### Approval details

|               |                                                                                     |                                                                                                                                                       |               |
|---------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| UL Recognized |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 240868 |
|---------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|

|     |                                                                                     |         |
|-----|-------------------------------------------------------------------------------------|---------|
| EAC |  | B.01742 |
|-----|-------------------------------------------------------------------------------------|---------|

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>