

IB IL 24 PWR IN/2F-D-2MBD-PAC

Order No.: 2863821

The illustration shows the version IB IL 24 PWR IN/F-PAC



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2863821>

Inline power terminal block, complete with accessories (connector and labeling field), 24 V DC, with fuse (main and segment voltage) and diagnostics, transmission speed 2 MBaud

Commercial data

GTIN (EAN)	4017918977726
sales group	K417
Pack	1 pcs.
Customs tariff	85389091
Weight/Piece	0.0838 KG
Catalog page information	Page 267 (AX-2009)

Product notes

WEEE/RoHS-compliant since:
07/06/2007



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Width	12.2 mm
Height	119.8 mm
Depth	71.5 mm

Inline potential routing

Current consumption from U_L	max. 45 mA DC
Supply for main circuit U_M	24 V DC -15% / +20% (in acc. with EN 61131-2) (nominal value)
Power supply for U_M	4 A (nominal value)
Segment power supply voltage U_S	24 V DC -15% / +20% (in acc. with EN 61131-2)
Power supply for U_S	4 A (nominal value)

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2010 Phoenix Contact
Technical modifications reserved;