

Electronic housing - ME 22,5 OT-MSTBO BU - 2908948

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)

Upper part of housing, for COMBICON connection, double-level.

Product Features

- ▼ Tool-free mounting
- When a device is unplugged from the system as a whole, the signal chain is not interrupted# Supply via standard MINI COMBICON plug
- ✓ Large assembly area
- Gold contacts for data transmission and power supply (125 V, 8 A)
- ME...TBUS connector with 5 parallel contacts can be snapped onto DIN rails to save space
- Same PCB geometry for all design widths
- Recessed labeling areas
- Fast mounting on DIN rails according to EN 60715
- ✓ Inflammability class V0 according to UL 94
- Cost savings thanks to easy device production
- Material and part identification embossed on the housing (recyclability)
- Functional earth ground contact (EMC) integrated in the housing base
- Metal foot catch
- ☑ Electronic components can be partially removed.
- optional BUS connection integrated in the housing, for either parallel or serial contacting

Key commercial data

Packing unit	11
Weight per Piece (excluding packing)	12.6 GRM
Custom tariff number	85472000
Country of origin	Germany

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27440208



Electronic housing - ME 22,5 OT-MSTBO BU - 2908948

Classifications

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Approvals

Approval	S
----------	---

Approvals

UL Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized **9**

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com