

Safety controller - RFC 470S PN 3TX - 2916794

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Remote field controller with 3 x 10/100 Ethernet, INTERBUS master, PROFINET controller with integrated PROFIsafe safety controller, PROFINET device, IP20 protection, plug-in parameterization memory

Your advantages

- ✓ Engineering with PC Worx (IEC 61131-3)
- ✓ Numerous protocols supported such as: HTTP, FTP, SNMP, SMTP, SQL, MySQL, etc.
- ✓ Integrated PROFINET controller and PROFINET device
- ✓ Integrated Ethernet interface
- ✓ Complete fieldbus master (8192 I/O points)
- ✓ Flash file system
- ✓ FTP server
- ✓ Integrated web server for visualization with WebVisit
- ✓ Safe analog value processing with SAFE AI and other components



Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4046356436045

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	124 mm
Height	185 mm
Depth	190 mm
Width	124 mm

Safety controller - RFC 470S PN 3TX - 2916794

Technical data

Dimensions

	124 mm
Height	185 mm
	210 mm
Depth	190 mm
	190 mm
Note on dimensions	without fan module
	With fan module

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 55 °C (from 45°C only with fan module)
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	10 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)
Air pressure (operation)	80 kPa ... 108 kPa (up to 2000 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (up to 3000 m above sea level)

Control system

Engineering tool	PC WORX
Programming languages supported	Programming in acc. with IEC 61131-3
Diagnostics tool	DIAG+, version 2.00 or higher

IEC 61131 runtime system

Engineering tool	PC WORX
Program memory	typ. 8 Mbyte
Mass storage	16 Mbyte
Retentive mass storage	240 kByte (NVRAM)
Number of control tasks	16
Realtime clock	Integrated (battery backup)

Fieldbus function

Amount of process data	max. 8192 Bit (INTERBUS)
Number of supported devices	max. 512 (of which 254 are remote bus devices/bus segments)
Number of devices with parameter channel	max. 126
Program memory	typ. 8 Mbyte

Data interfaces

Interface	INTERBUS (Master)
Number	1
Connection method	D-SUB-9 female connector
Transmission speed	500 kBaud / 2 MBaud (can be switched)
Interface	Parameterization/operation/diagnostics
Number	1

Safety controller - RFC 470S PN 3TX - 2916794

Technical data

Data interfaces

Connection method	D-SUB 9 plug
Interface	Ethernet
Number	3
Connection method	RJ45 jack
Transmission speed	10/100 Mbps

PROFINET

Device function	PROFINET-Controller
Specification	Version 1.1
Update rate	min. 1 ms

Direct I/Os

Input name	Digital inputs
Number of inputs	5
Connection method	14-pos. FLK pin strip
Connection technology	FLK cable connector (14-pos.)
Output name	Digital outputs
Number of outputs	3
Connection method	14-pos. FLK pin strip
Connection technology	FLK cable connector (14-pos.)

Power supply

Power supply connection	Screw terminal blocks, plug-in
Typical current consumption	1 A
Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC (including ripple)
Power dissipation	max. 24 W

Mechanical design

Weight	2000 g
Note on weight specifications	without fan module
Weight	2200 g
Note on weight specifications	with fan module
Diagnostics display	yes
Controller redundancy	No
Safety function	yes

General data

Processor	Intel® Celeron® 927 UE 1.5 GHz
-----------	--------------------------------

Standards and Regulations

Vibration (operation)	1g (Criterion 1, according to IEC 60068-2-6)
Shock (operation)	25g (Criterion 1, according to IEC 60068-2-27)

Environmental Product Compliance

Safety controller - RFC 470S PN 3TX - 2916794

Technical data

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 10.0.1	27242207
eCl@ss 4.0	27240400
eCl@ss 4.1	27240400
eCl@ss 5.0	27242700
eCl@ss 5.1	27242700
eCl@ss 6.0	27242200
eCl@ss 7.0	27242207
eCl@ss 8.0	27242207
eCl@ss 9.0	27242207

ETIM

ETIM 2.0	EC000236
ETIM 3.0	EC000236
ETIM 4.0	EC000236
ETIM 5.0	EC000236
ETIM 6.0	EC000236
ETIM 7.0	EC000236

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	39122114
UNSPSC 18.0	39122114
UNSPSC 19.0	39122114
UNSPSC 20.0	39122114
UNSPSC 21.0	39122114

Approvals

Approvals

Safety controller - RFC 470S PN 3TX - 2916794

Approvals

Approvals

Functional Safety / UL Listed / cUL Listed / Functional Safety / EAC / cULus Listed

Ex Approvals

Approval details

Functional Safety		IFA 1003001	
UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324
cUL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 140324
Functional Safety		IFA 1001017	
EAC		RU *- DE.A*30.B.00238	
cULus Listed			

Accessories

Accessories

Adapter

Adapter - PSM-AD-D9-NULLMODEM - 2708753



V.24 (RS-232) zero modem connector

Documentation

Safety controller - RFC 470S PN 3TX - 2916794

Accessories

Quick start guide - UM QS DE SAFETYPROG - 2888628



Quick Start Guide, German, for SafetyProg

Quick start guide - UM QS EN SAFETYPROG - 2888631



Quick Start Guide, English, for SafetyProg

Drivers and interfaces

Software - AX OPC SERVER - 2985945



AX OPC SERVER, communication interface for OPC-capable visualization with PC WORX-based controls.

Fan

Fan - RFC DUAL-FAN - 2730239



Fan module for Remote Field Controllers RFC 430 ETH-IB / RFC 450 ETH-IB

Parameterization memory

Memory - CF FLASH 256MB - 2988780



Program and configuration memory, plug-in, 256 MB

Safety controller - RFC 470S PN 3TX - 2916794

Accessories

Memory - CF FLASH 256MB APPLIC A - 2988793



Program and configuration memory, plug-in, 256 MB with license key for function block libraries, e.g., for SNMP, SQL, wireless, motion functions, etc.

Memory - CF FLASH 256MB PDPI BASIC - 2700549



Program and configuration memory, plug-in, 256 MB with license key for licensing the PDPI - BASIC function block for precise multi-channel controllers with self-optimization, additional functions: e.g., for heating and cooling functions or hydraulic movements.

Memory - CF FLASH 256MB PDPI PRO - 2700550



Program and configuration memory, plug-in, 256 MB with license key for licensing the PDPI - PRO function block for precise multi-channel controllers with self-optimization, additional functions: e.g., for setpoint processing, for heating and cooling functions.

Programming

Software - PC WORX DEMO - 2985725



Software package for PC-based automation solutions, PC WORX DEMO, contains all 5 IEC languages, with MSFC compiler, max. 16 bytes input and output data

Software - PC WORX BASIC LIC - 2985275



Software package for PC-based automation solutions, PC WORX BASIC license, contains all 5 IEC languages, without MSFC compiler, max. 2048 byte input and output data, version-specific license key

Safety controller - RFC 470S PN 3TX - 2916794

Accessories

Software - PC WORX PRO LIC - 2985385



Software package for PC-based automation solutions, PC WORX PRO license, contains all 5 IEC languages, with MSFC compiler, max 128 kB input and output data, version-specific license key

Software - SAFETYPROG BASIC - 2700443



Programming software for INTERBUS-Safety systems and PROFIsafe controllers from Phoenix Contact, with graphical user interface according to IEC 61131-3 in function block diagram (FBD), ladder diagram (LD), and structured text (ST).

One of the libraries from the corresponding PLCopen libraries (Basic_SF, MatHandling_SF, Muting_SF, SafeMode_SF, and TwoHand_SF) can be used per project.

Software - SAFETYPROG ADVANCED - 2700441



Programming software for INTERBUS-Safety systems and PROFIsafe controllers from Phoenix Contact, with graphical user interface according to IEC 61131-3 in function block diagram (FBD), ladder diagram (LD), and structured text (ST).

Three of the libraries from the corresponding PLCopen libraries (Basic_SF, MatHandling_SF, Muting_SF, SafeMode_SF, and TwoHand_SF) can be used per project.

Software - SAFETYPROG PROFESSIONAL - 2700442



Programming software for INTERBUS-Safety systems and PROFIsafe controllers from Phoenix Contact, with graphical user interface according to IEC 61131-3 in function block diagram (FBD), ladder diagram (LD), and structured text (ST).

All of the libraries from the corresponding PLCopen libraries (Basic_SF, MatHandling_SF, Muting_SF, SafeMode_SF, and TwoHand_SF) can be used per project.

Programming cable

Connecting cable - IBS PRG CAB - 2806862



Connection cable, to connect the controller boards to the PC (RS-232-C), length 3 m

Software library

Safety controller - RFC 470S PN 3TX - 2916794

Accessories

Function block - SAFE AI - 2400057



Function block library for safety-related analog value acquisition with standard I/O modules. Please contact the safety hotline (+49 5281 9-462777) before ordering the SAFE AI article.

Software add-on - PC WORX TARGET FOR SIMULINK - 2400041



Software add-on for integration and execution of MATLAB/Simulink models on Remote Field and Axioline controllers

Storage medium

USB memory stick - USB FLASH DRIVE - 2402809



USB memory stick, 8 GB

System cable

Cable - FLK 14/EZ-DR/ 200/KONFEK - 2288930



Round cable set; connection 1: IDC/FLK socket strip (1x 14-position); connection 2: IDC/FLK socket strip (1x 14-position); cable length: 2 m

Passive module - FLKMS 14/ 8IM/LA/PLC - 2284536



VARIOFACE sensor module, for connecting 8 p-n-p sensors, with LED

Safety controller - RFC 470S PN 3TX - 2916794

Accessories

Software - PC WORX PRO-MSFC LIC - 2985495



Software package for PC-based automation solutions, PC WORX PRO-MSFC license, contains all 5 IEC languages and MSFC compiler, max. 64 Kbytes IN, 64 Kbytes OUT, version-specific license key

Function block - SAFETYPROG2.X PLCOPEN BASIC - 2876067



Software library PLCOpen Basic, PLCOpen-conforming function block library to support the basic functionalities of safety engineering.

Software - SAFETYPROG2.X PLCOPEN TWOHAND - 2916846



Software library PLCOpen TwoHand, PLCOpen-compliant function block library, supports two-handed applications in safety engineering

Function block - SAFETYPROG 2.X MATHANDLING SF - 2985932



Function blocks for the conveying technology with the INTERBUS Safety system.

Software - SAFETYPROG2.X PLCOPEN MUTING - 2916862



Software library PLCOpen Muting, PLCOpen-conforming function block library to support the functionality of Muting of the safety engineering.

Safety controller - RFC 470S PN 3TX - 2916794

Accessories

Software - SAFETYPROG2.X PLCOPEN OSSD - 2916859



Software library PLCopen OSSD, PLCopen-conforming function block library, supports the electro-sensitive safety equipment in safety engineering

Software - SAFETYPROG2.X PLCOPEN SAFEMODE - 2916875



Software library PLCopen SafeMode, PLCopen-conforming function block library to support the functionality of SafeMode in safety engineering.

Necessary add-on products

Memory - CF FLASH 256MB - 2988780



Program and configuration memory, plug-in, 256 MB

Memory - CF FLASH 256MB APPLIC A - 2988793



Program and configuration memory, plug-in, 256 MB with license key for function block libraries, e.g., for SNMP, SQL, wireless, motion functions, etc.

Memory - CF FLASH 2GB - 2701185



Program and configuration memory, plug-in, 2 Gbytes.

Safety controller - RFC 470S PN 3TX - 2916794

Accessories

Memory - CF FLASH 2GB APPLIC A - 2701189



Program and configuration memory, plug-in, 2 Gbytes with license key for function block libraries, e.g., for: SNMP, SQL, wireless, motion functions, etc.

Memory - CF FLASH 256MB PDPI BASIC - 2700549



Program and configuration memory, plug-in, 256 MB with license key for licensing the PDPI - BASIC function block for precise multi-channel controllers with self-optimization, additional functions: e.g., for heating and cooling functions or hydraulic movements.

Memory - CF FLASH 256MB PDPI PRO - 2700550



Program and configuration memory, plug-in, 256 MB with license key for licensing the PDPI - PRO function block for precise multi-channel controllers with self-optimization, additional functions: e.g., for setpoint processing, for heating and cooling functions.

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>