

## Fuse plug - P-FU 5X20 - 3036806

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, connection method: Plug connection, nominal current: 6.3 A, nom. voltage: 500 V, width: 6.2 mm, fuse type: G / 5 x 20, mounting type: Plug-in mounting, color: black

### Your advantages

- ✓ Large-surface labeling option
- ✓ Test contacts on both sides of the fuse
- ✓ Versions with bipolar error display
- ✓ Can be used for overload/short-circuit protection

RoHS

COMPLETE RoHS

### Key Commercial Data

|              |                                                                                                         |
|--------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 10 pc                                                                                                   |
| GTIN         | <br>4 017918 943899 |
| GTIN         | 4017918943899                                                                                           |

### Technical data

#### General

|                                                 |                                                                                                     |
|-------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| Note                                            | Prior to replacing the cartridge fuse, disconnect the fuse connector from the basic terminal block. |
| Color                                           | black                                                                                               |
| Insulating material                             | PA                                                                                                  |
| Flammability rating according to UL 94          | V0                                                                                                  |
| Maximum power dissipation for nominal condition | 1.6 W                                                                                               |

#### Dimensions

|        |        |
|--------|--------|
| Width  | 6.2 mm |
| Length | 28 mm  |

#### General

|                     |            |
|---------------------|------------|
| Fuse                | G / 5 x 20 |
| Degree of pollution | 3          |

# Fuse plug - P-FU 5X20 - 3036806

## Technical data

### General

|                                                                         |                                                                       |
|-------------------------------------------------------------------------|-----------------------------------------------------------------------|
| Maximum load current                                                    | 6.3 A (the current is determined by the fuse used)                    |
| Nominal current $I_N$                                                   | 6.3 A (the current is determined by the fuse used)                    |
| Nominal voltage $U_N$                                                   | 500 V (The voltage is determined by the fuse or selected LED display) |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C                                                                |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C                                                                |
| Static insulating material application in cold                          | -60 °C                                                                |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed                                                                |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed                                                                |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed                                                                |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg                                                              |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3                                                           |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3                                                           |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3                                                           |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3                                                           |

### Connection data

|                   |                 |
|-------------------|-----------------|
| Connection method | Plug connection |
|-------------------|-----------------|

### Standards and Regulations

|                                        |     |
|----------------------------------------|-----|
| Connection in acc. with standard       | CSA |
| Flammability rating according to UL 94 | V0  |

### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Classifications

### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27142001 |
| eCl@ss 4.0    | 27142000 |
| eCl@ss 4.1    | 27142000 |
| eCl@ss 5.0    | 27142000 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27142000 |
| eCl@ss 7.0    | 27142001 |
| eCl@ss 8.0    | 27142001 |
| eCl@ss 9.0    | 27142001 |

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |

## Fuse plug - P-FU 5X20 - 3036806

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC002018 |
| ETIM 5.0 | EC000035 |
| ETIM 6.0 | EC000035 |
| ETIM 7.0 | EC000035 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121409 |
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121629 |
| UNSPSC 18.0   | 39121629 |
| UNSPSC 19.0   | 39121629 |
| UNSPSC 20.0   | 39121629 |
| UNSPSC 21.0   | 39121629 |

### Approvals

#### Approvals

#### Approvals

CSA / EAC / EAC / UL Recognized / cUL Recognized / cULus Recognized

#### Ex Approvals

#### Approval details

|                    |                                                                                     |                                                                                                                                         |       |
|--------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------|
| CSA                |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
| Nominal voltage UN |                                                                                     | 300 V                                                                                                                                   |       |
| Nominal current IN |                                                                                     | 10 A                                                                                                                                    |       |

|     |                                                                                     |               |
|-----|-------------------------------------------------------------------------------------|---------------|
| EAC |  | EAC-Zulassung |
|-----|-------------------------------------------------------------------------------------|---------------|

## Fuse plug - P-FU 5X20 - 3036806

### Approvals

|     |                                                                                   |                          |
|-----|-----------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.A*30.B.01742 |
|-----|-----------------------------------------------------------------------------------|--------------------------|

|                    |                                                                                   |                                                                                                                                                       |              |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| UL Recognized      |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 60425 |
|                    |                                                                                   |                                                                                                                                                       |              |
| Nominal voltage UN |                                                                                   | 300 V                                                                                                                                                 |              |
| Nominal current IN |                                                                                   | 10 A                                                                                                                                                  |              |

|                    |                                                                                   |                                                                                                                                                       |              |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| cUL Recognized     |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 60425 |
|                    |                                                                                   |                                                                                                                                                       |              |
| Nominal voltage UN |                                                                                   | 300 V                                                                                                                                                 |              |
| Nominal current IN |                                                                                   | 10 A                                                                                                                                                  |              |

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| cULus Recognized |  |
|------------------|-------------------------------------------------------------------------------------|

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>