

BTMM-106-01-T-S



SNT-100-BK-T-H



MNT-114-BK-G

SNT-100-BK-G



JL-300-25-T

SNT, MNT, 2SN, SNM, PK, JL, BTMM SERIES

(2.54 mm) .100"

# SHUNTS & JUMPERS

**SNT/MNT mates with:**  
TSW, HTSW, MTSW, HMTSW, TLW, DW, EW, ZW, HW, TSM, BST, PHT

**2SN mates with:**  
TMMH, TMM, MTMM, MMT, TW, LTMM, ZLTMM, TSH, EHT

**SNM mates with:**  
TMS, MTMS, DWM

## SPECIFICATIONS

For complete specifications see [www.samtec.com?SNT](http://www.samtec.com?SNT), [www.samtec.com?MNT](http://www.samtec.com?MNT), [www.samtec.com?2SN](http://www.samtec.com?2SN), [www.samtec.com?SNM](http://www.samtec.com?SNM)

**Insulator Material:** Glass Filled Polyester  
**Contact Material:** Phosphor Bronze  
**Current Rating (SNT/TSW):** SNT=4.3 A per pin (1 pin powered per row)  
**Current Rating (MNT/TSM):** MNT=3.9 A per pin (1 pin powered per row)  
**Operating Temp Range:** -55 °C to +125 °C  
**Working Voltage:** MNT: 450 VAC  
**Insertion Depth:** SNT=(4.32 mm) .170" min. 2SN=(2.29 mm) .090" min. SNM=(3.43 mm) .135" min.  
**Lead Size accepted:** SNT= (0.64 mm) .025" SQ 2SN= (0.51 mm) .020" SQ  
**RoHS Compliant:** Yes

## RECOGNITIONS

For complete scope of recognitions see [www.samtec.com/quality](http://www.samtec.com/quality)



<b>SNT</b>	<b>100</b>	<b>BODY COLOR</b>	<b>PLATING OPTION</b>	<b>HANDLE OPTION</b>
		-BK = Black	-G = 10 μ" (0.25 μm) Gold	-H = Handle (Black Only)
		-OR = Orange	-T = Tin	
		-RD = Red	<b>Note:</b> Other Gold plating options available. Contact Samtec.	
		-BL = Blue		
		-YW = Yellow		

### JL

Insulation is white Teflon

(0.64) .025 DIA REF

(3.18) .125

(14.00) .550

(6.10) .240

<b>MNT</b>	<b>1</b>	<b>NO. OF POSITIONS</b>	<b>BODY COLOR</b>	<b>PLATING OPTION</b>
		<b>02 thru 20</b>	-BK = Black	-G = 10 μ" (0.25 μm) Gold
			-T = Tin	
		(2.54) .100 X No. of Positions		

### BTMM

(0.50) .020 SQ

(2.57) .101

(4.00) .157

(8.00) .315

(2.60) .102

FILE NO. E111594

**Note:** Some lengths, styles and options are non-standard, non-returnable.

**JL**  
For complete specifications see [www.samtec.com?JL](http://www.samtec.com?JL)

Part No.	A
JL-100-25-T	(2.54) .100
JL-250-25-T	(6.35) .250
JL-300-25-T	(7.62) .300
JL-400-25-T	(10.16) .400
JL-500-25-T	(12.70) .500
JL-600-25-T	(15.24) .600
JL-1000-25-T	(25.40) 1.000

### 2SN

Part No. 2SN-BK-G

(2.00) .0787

(3.99) .157

(1.02) .040

(4.45) .175

(2.00) .0787

### SNM

Part No. SNM-100-BK-G

(2.54) .100

(1.27) .050

(3.30) .130

### PK

Part No.	A	B
PK-01-06	(0.64) .025 SQ	(5.84) .230
PK-01-07	(0.51) .020 SQ	(3.18) .125

**Insulator Material:** Natural Thermoplastic  
**Note:** Order per wheel. 6 pins per wheel.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.