
REVISION J


TABLE 1						
PART NUMBER	CABLE PART NUMBER	"A" REF (SEE NOTE 16)	"B" ± 50[2.0] (SEE NOTE 17)	Ø "C" REF		
SCPU-17-G-2.00, -AMS, -AM, -BMS, -BM	UCA-02-01	2.00M [78.74]	2.04M [80.18]	4.8[.189]		
SCPU-17-G-3.00, -AMS, -AM, -BMS, -BM	UCA-03-01	3.00M [118.11]	3.04M [119.55]	5.0[.197]		
SCPU-17-G-5.00, -AMS, -AM, -BMS, -BM	UCA-03-01	5.00M [196.85]	5.04M [198.29]	5.2[.205]		
SCPU-17-G-2.00, -BC	UCA-02-01	2.00M [78.74]	2.02M [79.53]	4.8[.189]		
SCPU-17-G-3.00, -BC	UCA-03-01	3.00M [118.11]	3.02M [118.90]	5.0[.197]		
SCPU-17-G-5.00, -BC	UCA-03-01	5.00M [196.85]	5.02M [197.64]	5.2[.205]		





DESIGNED & DIMENSIONED IN MILLIMETERS[INCHES]

SCPU-17-G-X.XX-AMS-BMS SHOWN









SCPU-17-X-X.XX-XXX-XXX **PLATING** -G: .000030" GOLD ON CONTACT AREAS, NICKEL ON SHELLS **LENGTH**

-X.XX ("A", SEE TABLE 1) (0.17M[6.69] MIN - 5.00M[196.85] MAX

END 1 OPTIONS

-AMS: SEALED USB A (USB A END SEALED ONLY) -BMS: SEALED USB B (USB B END SEALED ONLY)

NOTE:

-2.00, -3.00, AND -5.00 ARE CATALOG STANDARD LENGTHS. FOR OTHER LENGTHS (0.17M[6.69] MIN - 5.00M[196.85] MAX) CONTACT SAMTEC.

- END 2 OPTIONS

(USB A END SEALED ONLY)

(USB B END SEALED ONLY)

(USB A END NOT SEALED ONLY)

(USB B END NOT SEALED ONLY)

-AMS: SEALED USB A

-BMS: SEALED USB B

-BC: BLUNT CUT

(SEE SHEET3)

-am: USB a not sealed

-BM: USB B NOT SEALED




TABLE 6			
LENGTH RANGE	USE CABLE PART No.	O.D.	
0.17M - 1.99M	UCA-01-XX	4.80	
2.00M - 2.99M	UCA-02-XX	5.00	
3.00M - 5.00M	UCA-03-XX	5.20	

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS.

TOLERANCES ARE: **DECIMALS** 0.X: ±0.35 [.014] 0.XX: ±0.25 [.010] 0.XXX: ±0.15 [.006]

PROPRIETARY NOTE THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN

CONSENT OF SAMTEC, INC

SHEET SCALE: 1:1.3333

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail: info@SAMTEC.com

BY: CHAD F

SEALED CIRCULAR CABLE PLUG, USB

SCPU-17-X-X.XX-XXX-XXX 12/8/2004

SHEET 1 OF 10

INSULATOR: GLASS FILLED THERMOPLASTIC CONTACTS: COPPER ALLOY
SHIELDS: CRS. CABLE NUT: PA66
SEALED PREMOLD: LDPE/ SHOT WEIGHT 10.66 g [.0235 lb]

NON-SEALED PREMOLD: N/A SEALED OVERMOLD: PA66 GF13 FR/ SHOT WEIGHT 12.71 g [.0280 lb] NON SEALED OVERMOLD: PVC/ SHOT WEIGHT: 9.07 g [.0200 lb]

:\DWG\MISC\MKTG\SCPU-17-X-X.XX-XXX-XXX-MKT.SLDDRV

16. X.XX LENGTH IS EQUAL TO LENGTH ("A"). 17. FOR ALL LENGTHS TOLERANCE SHALL BE ± 2% OF LENGTH 18. ASSEMBLY TO BE SHIPPED IN BULK PACKAGING.

REPRESENTS A CRITICAL DIMENSION.

NOTES:

2. NOTE DELETED.

14. ALL DRAFT MUST BE WITHIN THE SPECIFIED TOLERANCES.

10. MOLD TO BE INSERTED TO ACCEPT DIFFERENT CABLE DIAMETERS.

15. ALL INSIDE/OUTSIDE RADII 0.13 MAX UNLESS OTHERWISE STATED.

AFTER FINAL ELECTRICAL TEST, LABEL EACH ASSEMBLY WITH 1 LABEL-ET.

19. THIS IS A COMPONENT OF USBP-A-01-G-B-01 (CALLED OUT ON THE BOM), BUT LABELLED INDIVIDUALLY FOR ASSEMBLY PURPOSES.
20. THIS IS A COMPONENT OF USBP-B-01-G-B-01 (CALLED OUT ON THE BOM), BUT LABELLED INDIVIDUALLY FOR ASSEMBLY PURPOSES.

13. ANY ADDITIONAL VOIDING AND/OR MODIFICATIONS TO VOIDING MUST BE APPROVED BY SAMTEC PRODUCT ENGINEERING.

21. TORQUE SPECIFICATION FOR SCN-17-01 IS 12 IN-LBS.


SINK AREAS, VOIDS, OR OTHER BLEMISHES.


8. ALL MUTIPLE CAVITY MOLDS SHALL IDENTIFY EACH CAVITY WITH A NUMBER DESIGNATION LOCATED WHERE SHOWN.

9. ALL IDENTIFICATION MARKS MUST NOT STAND GREATER THAN 0.051 [.002] OFF THE SURFACE OF THE PART.

FINISHED ASSEMBLY TO BE 100% TESTED FOR OPENS AND SHORTS BEFORE PREMOLD AND AFTER FINAL ASSEMBLY.

12. ALL EJECTOR PIN AND GATE LOCATIONS MUST BE APPROVED BY SAMTEC PRODUCT ENGINEERING.







PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO ASAMTE, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USEP FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 1:1.33333

samtec

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail: info@SAMTEC.com code: 55322


DESCRIPTION:


SEALED CIRCULAR CABLE PLUG, USB


DWG NO

SCPU-17-X-X.XX-XXX-XXX

BY: CHAD F 12/8/2004 SHEET 2 OF 10







01

02 03

04





TABLE	TABLE 3 - PIN-OUT		
POS	WIRE COLOR		
01	RED		
02	WHITE		
03	GREEN		
04	BLACK		




RED WHITE

GREEN


BLACK



IN-PROCESS 9 CRIMP SHELLS OVER BRAID AND ADD SOLDER SHIELD TO SHELL THEN FOLD GROUND WIRE "TWISTED SHIELD" OVER CRIMP AND SOLDER TO SHELL



IN-PROCESS 8 ADD USBS-A-N-02-01 (SEE NOTE 19) & USBS-B-N-02-01 (SEE NOTE 20) SHELLS



PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 1:1.33333



520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail: info@SAMTEC.com code: 55322

DESCRIPTION


SEALED CIRCULAR CABLE PLUG, USB


SCPU-17-X-X.XX-XXX-XXX


12/8/2004 BY: CHAD F

SHEET 5 OF 10


F:\DWG\MISC\MKTG\SCPU-17-X-X.XX-XXX-XXX-MKT.SLDDRW








IN-PROCESS VIEWS FOR -AMS AND -BC END OPTIONS **REVISION J** IN-PROCESS 5 TERMINATE TO SUB-USB-A-G-B-01 (SEE NOTE 19) (SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 5, UNLESS OTHERWISE STATED) IN-PROCESS 6 ADD USBS-A-N-01-01 SHELL **TABLE 4 - PIN-OUT** (SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 7, UNLESS OTHERWISE STATED) 2 x "B" +2.00 REF (SEE TABLE 1) POS WIRE COLOR $(2 \times "B" = "A" + 36.5[1.45])$ 01 RED NOTE 16 & 17) 02 WHITE 03 **GREEN** 04 **BLACK** UCA-XX-XX USBS-A-N-01-01 (SEE TABLE 1) (SEE NOTE 19) **IN-PROCESS 8 IN-PROCESS 7** CRIMP SHELLS OVER BRAID ADD USBS-A-N-02-01 SHELL (SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 9, UNLESS OTHERWISE STATED) (SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 8, UNLESS OTHERWISE STATED) USBS-A-N-02-01 (SEE NOTE 19) П IN-PROCESS 10 ADD SCN-17-01 IN-PROCESS 9 (SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 11, UNLESS OTHERWISE STATED) PREMOLDING (SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 10, UNLESS OTHERWISE STATED) SCN-17-01 (2 PLCS) PREMOLD (TYP) **IN-PROCESS 12**





PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR LISED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 1:1.33333

520 PARK EAST BLVD, NEW ALBANY, IN 47150 PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail: info@SAMTEC.com

DESCRIPTION

SEALED CIRCULAR CABLE PLUG, USB

SCPU-17-X-X.XX-XXX-XXX

BY: CHAD F 12/8/2004 SHEET 9 OF 10

F:\DWG\MISC\MKTG\SCPU-17-X-X.XX-XXX-XXX-MKT.SLDDRW

REVISION J

IN-PROCESS VIEWS FOR -BMS AND -BC END OPTION








TABLE 5 - PIN-OUT		
POS	WIRE COLOR	
01	RED	
02	WHITE	
03	GREEN	
04	BLACK	



IN-PROCESS 7

ADD USBS-B-N-02-0T SHELL (SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 8, UNLESS OTHERWISE STATED)





IN-PROCESS 8 CRIMP SHELLS OVER BRAID (SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 9, UNLESS OTHERWISE STATED)



IN-PROCESS 9


PREMOLDING (SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 10, UNLESS OTHERWISE STATED)






IN-PROCESS 11 OVERMOLD

(SAME AS -AMS AND -BMS END OPTIONS IN-PROCESS 12, UNLESS OTHERWISE STATED)





PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR LISED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 1:1.33333



PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail: info@SAMTEC.com

DESCRIPTION

SEALED CIRCULAR CABLE PLUG, USB

SCPU-17-X-X.XX-XXX-XXX

BY: CHAD F

12/8/2004

SHEET 10OF 10

F:\DWG\MISC\MKTG\SCPU-17-X-X.XX-XXX-XXX-MKT.SLDDRW