

TDA7708

AM/FM/HD-Radio[™] radio receiver IC

Data brief



Features

- Fully automotive grade CMOS design
- AM/FM Band
- Low-IF, DSP-based architecture
- Very high dynamic range built-in IF-ADC
- Minimum external component count
- Very small footprint package
- Optional Multipath noise mitigation processing
- Compatible with HD-Radio™
- Digital Audio Output
- Fully RoHS-compliant

Description

The TDA7708 is a single chip fully-CMOS AM/FM single-channel tuner for terrestrial radio receiver applications.

The TDA7708 features multiple front-end lownoise amplifiers (LNAs) to cover AM LW/MW/SW bands, and the entire FM band, with advanced DSP-controlled automatic gain control (AGC) amplifier and mixer stages.

After on-chip IF filtering, the TDA7708 digitizes the signal with a very high dynamic range ADC; it processes the complex phase-quadrature baseband signal allowing applications like multipath noise mitigation, and integrated RDS decoding. The TDA7708 furthermore integrates the HD-Radio[™] channel filtering.

Besides providing optimal AM/FM quality reception, the TDA7708 allows to realize a complete HD-Radio[™] receiver solution (in combination with the external STA680 HD-Radio[™] digital decoder coprocessor), with a low bill of material, high performance and automotive grade quality and reliability.

TDA7708 is pin-to-pin compatible with ST's dualchannel tuner TDA7707, allowing efficient design of scalable terrestrial radio-receiver platforms.

Order code	Package	Packing
TDA7708	VFQFPN64 (9 x 9 x 0.85 mm)	Тгау

For further information contact your local STMicroelectronics sales office.

Contents

1	Block and typical application diagrams	3
2	Package information	5
3	Revision history	6



1 Block and typical application diagrams



Figure 1. Block diagram

Table 2. Main features list

Features list		
Number of Channels	1	
Reception Band	AM/FM	
AM/FM Weak-Signal-Processing	\checkmark	
RDS decoder	\checkmark	
HD-Radio™ 1.0	Supported ⁽¹⁾	
Base Band Interface	12S	
VICS interface	\checkmark	
Control interface	I2C/SPI	
Digital Audio out	\checkmark	
Stereo audio DAC	\checkmark	

1. With external coprocessor.





Figure 2. Typical AM/FM application with optional STA680 HD-Radio[™] decoder

Table 3. A	Absolute	maximum	ratings
------------	----------	---------	---------

Symbol	Parameter	Min	Тур	Max	Units
Vs	Supply voltage	3.15	3.3	3.45	V
P _{tot}	Power dissipation	-	0.75 ⁽¹⁾	-	W
T _{amb}	Ambient temparature range		-40 to +85		°C

1. Typical use-case.



2 Package information

In order to meet environmental requirements, ST (also) offers these devices in ECOPACK[®] packages. ECOPACK[®] packages, are lead-free. The category of second Level Interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label.

ECOPACK[®] is an ST trademark. ECOPACK[®] specifications are available at: *www.st.com*.



Figure 3. VFQFPN64 mechanical data and package dimensions

Package is compliant to IPC/JEDEC J-STD-020D June 2007 standard Moisture/Reflow Sensitivity Classification for Nonhermetic Solid State Surface Mount Devices", MSL Level 3.



3 Revision history

Table 4. Document revision history

Date	Revision	Changes
16-Dec-2014	1	Initial release.



IMPORTANT NOTICE - PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2014 STMicroelectronics – All rights reserved



DocID027311 Rev 1