



■ 120x120x38



Model	Bearing ● VAPO	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
MEC0381V1-0000-A99	●	12	833	10.0	3100	138	0.36	48.0	218.0
MEC0381V2-0000-A99	●	12	421	5.1	2600	116	0.26	44.0	218.0
MEC0381V3-0000-A99	●	12	241	2.9	2100	93	0.18	37.0	218.0
MEC0382V1-0000-A99	●	24	383	9.2	3100	138	0.36	48.0	218.0
MEC0382V2-0000-A99	●	24	224	5.4	2600	116	0.26	44.0	218.0
MEC0382V3-0000-A99	●	24	130	3.1	2100	93	0.18	37.0	218.0
MEC0384V1-0000-A99	●	48	203	9.7	3100	138	0.36	48.0	218.0
MEC0384V2-0000-A99	●	48	120	5.8	2600	116	0.26	44.0	218.0
MEC0384V3-0000-A99	●	48	69	3.3	2100	93	0.18	37.0	218.0

Model	Bearing ⊙ 2BALL	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
EEC0381B1-0000-A99	⊙	12	833	10.0	3100	138	0.36	48.0	214.0
EEC0381B2-0000-A99	⊙	12	421	5.1	2600	116	0.26	44.0	214.0
EEC0381B3-0000-A99	⊙	12	241	2.9	2100	93	0.18	37.0	214.0
EEC0382B1-0000-A99	⊙	24	383	9.2	3100	138	0.36	48.0	214.0
EEC0382B2-0000-A99	⊙	24	224	5.4	2600	116	0.26	44.0	214.0
EEC0382B3-0000-A99	⊙	24	130	3.1	2100	93	0.18	37.0	214.0
EEC0384B1-0000-A99	⊙	48	203	9.7	3100	138	0.36	48.0	214.0
EEC0384B2-0000-A99	⊙	48	120	5.8	2600	116	0.26	44.0	214.0
EEC0384B3-0000-A99	⊙	48	69	3.3	2100	93	0.18	37.0	214.0

* If you need special specification. Please contact Sunon sales.

* Specifications are subject to change without notice. Specifications in this catalog are for reference.