

- UL Recognized File # E-520034
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition

DBL

MECHANICAL DATA

Case: Molded plastic body

Molding compound, UL flammability classification rating 94V-0



Base P/N with suffix "G" on packing code - halogen-free

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test

Polarity: Polarity as marked on the body

Weight: 0.38 g (approximately)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	DBL	DBL	DBL	DBL	DBL	DBL	DBL	
		201G	202G	203G	204G	205G	206G	207G	
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	700	
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	
Maximum average forward rectified current	I _{F(AV)}	2.0							
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load	I _{FSM}	50							
Rating for fusing (t<8.3ms)	I ² t	10.3							
Maximum instantaneous forward voltage (Note 1) I _F = 2 A	V _F	1.15							
Maximum DC reverse current at rated DC blocking voltage	I _R						2 500		
Typical thermal resistance	R _{θjL}						15		
	R _{θjA}						40		
Operating junction temperature range	T _J	- 55 to +150							
Storage temperature range	T _{STG}	- 55 to +150							

Note 1: Pulse Test with PW=300μs, 1% Duty Cycle

EXAMPLE

PREFERRED P/N	PART NO.	PACKING CODE	GREEN COMPOUND CODE	DESCRIPTION
DBL207G C1	DBL207G	C1		
DBL207G C1G	DBL207G	C1	G	Green compound

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG. 1 FORWARD CURRENT DERATING CURVE




FIG. 2 TYPICAL REVERSE CHARACTERISTICS




FIG. 3 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT







FIG. 4 TYPICAL FORWARD CHARACTERISTICS





PACKAGE OUTLINE DIMENSIONS



DIM.	Unit (mm)		Unit (in)	
	Min	Max	Min	Max
A	6.20	6.50	0.244	0.256
B	7.24	8.00	0.285	0.315
C	8.12	8.51	0.320	0.335
D	2.40	2.60	0.094	0.102
E	0.89	1.14	0.035	0.045
F	0.46	0.58	0.018	0.023
G	5.00	5.20	0.197	0.205
H	1.39	1.90	0.055	0.075
I	1.27	2.03	0.050	0.080
J	3.81	4.69	0.150	0.185
K	0.22	0.33	0.009	0.013
L	7.60	8.90	0.299	0.350

MARKING DIAGRAM



- P/N = Specific Device Code
- G = Green Compound
- YW = Date Code
- F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, of any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to indemnify TSC for any damages resulting from such improper use or sale.

Document Number: DS_D1311014

Ve