



SAW Components

SAW Rx 2in1 input diplex filter

GSM900 / GSM1800

Series/type:	B9522
Ordering code:	B39182B9522P810
Date:	December, 12, 2013
Version:	2.1


Datasheet

Application


- Low-loss 2in1 RF filter for mobile telephone GSM 900 and GSM 1800 systems, receive path (Rx)
- Usable passband:
 - Filter 1 (GSM 900): 35 MHz
 - Filter 2 (GSM 1800): 75 MHz
- Unbalanced to unbalanced operation for both filters
- Low amplitude ripple
- Suitable for GPRS class 1 to 12


Features

- Package size 1.8 x 1.4 x 0.68 mm³
- RoHS compatible
- Approx. weight 0.006g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**
- **Moisture Sensitivity Level 3**


Pin configuration

- 1 Input [Diplex]
- 6 Output [Filter 2]
- 9 Output [Filter 1]
- 2,3,5,10 Case ground
- 4,7,8 To be ground



Datasheet

Characteristics of Filter 1 (GSM900)

Temperature range for specification: $T = -20\text{ °C to }+85\text{ °C}$
 Terminating source impedance: $Z_S = 50\ \Omega \parallel 4.7\text{nH}$
 Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	942.5	—	MHz
Maximum insertion attenuation	α_{\max}	—	2.3	3.0	dB
925.0 ... 960.0 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	1.0	1.8	dB
925.0 ... 960.0 MHz					
Input VSWR		—	2.0	2.4	
925.0 ... 960.0 MHz					
Output VSWR		—	2.0	2.4	
925.0 ... 960.0 MHz					
Attenuation	α				
10.0 ... 480.0 MHz		45	61	—	dB
480.0 ... 850.0 MHz		30	32	—	dB
850.0 ... 905.0 MHz		23	25	—	dB
905.0 ... 914.0 MHz		10	19	—	dB
980.0 ... 1850.0 MHz		21	27	—	dB
1850.0 ... 1920.0 MHz		22	24	—	dB
1920.0 ... 3700.0 MHz		18	20	—	dB
3700.0 ... 6000.0 MHz		15	19	—	dB



Maximum ratings of Filter 1

Operable temperature range	T	-40/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 1 pulse
Input power at				
GSM 850, GSM 900	P _{IN}	15	dBm	effective power in the on-state, duty cycle 4:8, 10 000 hours
GSM 1800, GSM 1900	P _{IN}	3	dBm	
Tx bands				


¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.



Transfer function of Filter 1 (GSM900)



Transfer function of Filter 1 (GSM900) - Wideband




Datasheet




Smith charts of Filter 1


S₁₁ function




normal impedance: 50.00 Ω



S₂₂ function



normal impedance: 50.00 Ω



Datasheet

Characteristics of Filter 2 (GSM1800)

Temperature range for specification: $T = -20\text{ }^{\circ}\text{C to }+85\text{ }^{\circ}\text{C}$
 Terminating source impedance: $Z_S = 50\Omega \parallel 4.7\text{nH}$
 Terminating load impedance: $Z_L = 50\Omega$

		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	1842.5	—	MHz
Maximum insertion attenuation	α_{\max}	—	2.6	4.0	dB
1805.0 ... 1880.0 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	1.1	2.6	
1805.0 ... 1880.0 MHz					
Input VSWR		—	2.1	2.6	
1805.0 ... 1880.0 MHz					
Output VSWR		—	2.1	2.6	
1805.0 ... 1880.0 MHz					
Attenuation	α				
10.0 ... 940.0 MHz		30	44	—	dB
940.0 ... 1705.0 MHz		28	33	—	dB
1705.0 ... 1785.0 MHz		12	16	—	dB
1920.0 ... 1980.0 MHz		18	23	—	dB
1980.0 ... 2030.0 MHz		26	28	—	dB
2030.0 ... 2400.0 MHz		32	34	—	dB
2400.0 ... 2500.0 MHz		32	36	—	dB
2500.0 ... 2775.0 MHz		32	36	—	dB
2775.0 ... 5000.0 MHz		26	29	—	dB
5000.0 ... 6000.0 MHz		24	27	—	dB

Datasheet



Maximum ratings of Filter 2

Operable temperature range	T	-40/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 1 pulse
Input power at				
GSM 850, GSM 900	P _{IN}	15	dBm	effective power in the on-state, duty cycle 4:8, 10 000 hours
GSM 1800, GSM 1900	P _{IN}	3	dBm	
Tx bands				


¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.



Transfer function of Filter 2 (GSM1800)



Transfer function of Filter 2 (GSM1800) - Wideband




Datasheet




Smith charts of Filter 2


S_{11} function




normal impedance: 50.00 Ω



S_{22} function



normal impedance: 50.00 Ω



Datasheet



References

Type	B9522
Ordering code	B39182B9522P810
Marking and package	C61157-A7-A152
Packaging	F61074-V8226-Z000
Date codes	L_1126
S-parameters	B9522_LB_NB.s2p , B9522_LB_WB.s2p B9522_UB_NB.s2p , B9522_UB_WB.s2p see file header for port/pin assignment table
Soldering profile	S_6001
RoHS compatible	RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8th, 2011, on the restriction of the use of certain hazardous substances in electrical and electronic equipment ("Directive") with due regard to the application of exemptions as per Annex III of the Directive in certain cases.
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm for a large variety of matching coils.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Systems, Acoustics, Waves Business Group
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2013. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CeraLink, CeraPlas, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FilterCap, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.