



## **SAW Components**

### **SAW Rx 2in1 input diplex filter**

GSM1800 / GSM1900

<b>Series/type:</b>	<b>B9514</b>
<b>Ordering code:</b>	<b>B39202B9514P810</b>
<b>Date:</b>	<b>February 01, 2011</b>
<b>Version:</b>	<b>2.0</b>


### Application

- Low-loss 2in1 RF filter for mobile telephone GSM1900 and GSM1800 systems, receive path (Rx)
- Usable passband:  
Filter 1 (GSM1800): 75 MHz  
Filter 2 (GSM1900): 60 MHz
- Unbalanced to balanced operation for both filters
- Impedance transformation from 50  $\Omega$  to 150  $\Omega$  for both filters
- Low amplitude ripple
- Suitable for GPRS class 1 to 12




### Features

- Package size 1.8 x 1.4 x 0.68 mm<sup>3</sup>
- RoHS compatible
- Approx. weight 0.006g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**
- **Moisture Sensitive Level 3**



### Pin configuration

- 1 Input [Diplex]
- 8,9 Output balanced [Filter 1]
- 6,7 Output balanced [Filter 2]
- 2,3,4,5,10 Case-ground





# SAW Components

B9514

## SAW Rx 2in1 input duplex filter

1842.5 / 1960.0 MHz

### Data sheet



### Characteristics of Filter 1 (GSM1800)

Temperature range for specification:

$$T = -30\text{ °C to }+85\text{ °C}$$

Terminating source impedance:

$$Z_S = 50\ \Omega \parallel 3.3\text{nH}$$

Terminating load impedance:

$$Z_L = 150\ \Omega \parallel 15\text{nH (balanced)}$$

		min.	typ. @ 25 °C	max.	
<b>Center frequency</b>	$f_c$	—	1842.5	—	MHz
<b>Maximum insertion attenuation</b> 1805.0 ... 1880.0 MHz	$\alpha_{\max}$	—	2.1	2.8	dB
<b>Amplitude ripple (p-p)</b> 1805.0 ... 1880.0 MHz	$\Delta\alpha$	—	0.8	1.6	dB
<b>Input VSWR</b> 1805.0 ... 1880.0 MHz		—	1.5	2.2	
<b>Output VSWR</b> 1805.0 ... 1880.0 MHz		—	1.8	2.3	
<b>CMRR</b> ( $ S_{21}-S_{31} / S_{21}+S_{31} $ ) 1805.0 ... 1880.0 MHz		20	23	—	dB
<b>Attenuation</b> 10.0 ... 940.0 MHz	$\alpha$	45	55	—	dB
940.0 ... 1705.0 MHz		20	38	—	dB
1705.0 ... 1785.0 MHz		12	17	—	dB
1920.0 ... 1980.0 MHz		17	25	—	dB
1980.0 ... 2030.0 MHz		25	30	—	dB
2030.0 ... 2700.0 MHz		28	34	—	dB
2700.0 ... 6000.0 MHz		30	43	—	dB



SAW Components		B9514
SAW Rx 2in1 input duplex filter		1842.5 / 1960.0 MHz
Data sheet	SMD	

#### Maximum ratings of Filter 1

Operable temperature range	T	−40/+85	°C	
Storage temperature range	T <sub>stg</sub>	−40/+85	°C	
DC voltage	V <sub>DC</sub>	5	V	
ESD voltage	V <sub>ESD</sub>	50 <sup>1)</sup>	V	machine model, 1 pulse
Input Power at				
GSM 850, GSM 900	P <sub>IN</sub>	15	dBm	effective power in the on-state, duty cycle 4:8
GSM 1800, GSM 1900	P <sub>IN</sub>	15	dBm	
Tx bands				

<sup>1)</sup> acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.



## SAW Components

B9514


### SAW Rx 2in1 input duplex filter

1842.5 / 1960.0 MHz


#### Data sheet



#### Transfer function Filter 1 (GSM1800)





#### Transfer function Filter 1 (GSM1800) - Wideband





Smith charts Filter 1 (GSM1800)

$S_{11}$  function



$S_{22}$  function





# SAW Components

B9514

## SAW Rx 2in1 input duplex filter

1842.5 / 1960.0 MHz

### Data sheet



#### Characteristics of Filter 2 (GSM1900)

Temperature range for specification:  $T = -30\text{ °C to }+85\text{ °C}$   
Terminating source impedance:  $Z_S = 50\ \Omega \parallel 3.3\text{nH}$   
Terminating load impedance:  $Z_L = 150\ \Omega \parallel 18\text{nH (balanced)}$

		min.	typ. @ 25 °C	max.	
<b>Center frequency</b>	$f_c$	—	1960.0	—	MHz
<b>Maximum insertion attenuation</b> 1930.0 ... 1990.0 MHz	$\alpha_{\max}$	—	2.1	3.0	dB
<b>Amplitude ripple (p-p)</b> 1930.0 ... 1990.0 MHz	$\Delta\alpha$	—	0.9	1.8	dB
<b>Input VSWR</b> 1930.0 ... 1990.0 MHz		—	1.5	2.1	
<b>Output VSWR</b> 1930.0 ... 1990.0 MHz		—	1.8	2.1	
<b>CMRR</b> ( $ S_{21}-S_{31} / S_{21}+S_{31} $ ) 1930.0 ... 1990.0 MHz		22	28	—	dB
<b>Attenuation</b>	$\alpha$				
10.0 ... 1510.0 MHz		40	46	—	dB
1510.0 ... 1830.0 MHz		30	34	—	dB
1830.0 ... 1850.0 MHz		23	32	—	dB
1850.0 ... 1890.0 MHz		18	30	—	dB
1890.0 ... 1910.0 MHz		9	14	—	dB
2010.0 ... 2070.0 MHz		4	16	—	dB
2070.0 ... 2400.0 MHz		21	36	—	dB
2400.0 ... 6000.0 MHz		30	38	—	dB



SAW Components		B9514
SAW Rx 2in1 input duplex filter		1842.5 / 1960.0 MHz
Data sheet	SMD	

#### Maximum ratings of Filter 2



Operable temperature range	T	−40/+85	°C	
Storage temperature range	T <sub>stg</sub>	−40/+85	°C	
DC voltage	V <sub>DC</sub>	5	V	
ESD voltage	V <sub>ESD</sub>	50 <sup>1)</sup>	V	machine model, 1 pulse
Input Power at				
GSM 850, GSM 900	P <sub>IN</sub>	15	dBm	effective power in the on-state, duty cycle 4:8
GSM 1800, GSM 1900	P <sub>IN</sub>	15	dBm	
Tx bands				

<sup>1)</sup> acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.







**SAW Components****B9514****SAW Rx 2in1 input duplex filter****1842.5 / 1960.0 MHz**

Data sheet

**Transfer function Filter 2 (GSM1900)****Transfer function Filter 2 (GSM1900) - Wideband**

Please read *cautions and warnings* and *important notes* at the end of this document.





<b>SAW Components</b>	<b>B9514</b>
<b>SAW Rx 2in1 input duplex filter</b>	<b>1842.5 / 1960.0 MHz</b>
<b>Data sheet</b>	<b>SMD</b>

## References

<b>Type</b>	B9514
<b>Ordering code</b>	B39202B9514P810
<b>Marking and package</b>	C61157-A7-A152
<b>Packaging</b>	F61074-V8226-Z000
<b>Date codes</b>	L_1126
<b>S-parameters</b>	B9514_LB_NB.s3p, B9514_LB_WB.s3p B9514_UB_NB.s3p, B9514_UB_WB.s3p See file header for port/pin assignment table.
<b>Soldering profile</b>	S_6001
<b>RoHS compatible</b>	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
<b>Matching coils</b>	See Inductor pdf-catalog <a href="http://www.tdk.co.jp/tefe02/coil.htm#aname1">http://www.tdk.co.jp/tefe02/coil.htm#aname1</a> and Data Library for circuit simulation <a href="http://www.tdk.co.jp/etvcl/index.htm">http://www.tdk.co.jp/etvcl/index.htm</a>

For further information please contact your local EPCOS sales office or visit our webpage at [www.epcos.com](http://www.epcos.com).

**Published by EPCOS AG**  
**Surface Acoustic Wave Components Division**  
**P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2011. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



## Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet ([www.epcos.com/material](http://www.epcos.com/material)). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at [www.epcos.com/trademarks](http://www.epcos.com/trademarks).