

Not EU RoHS or ELV Compliant

- HMB Half-Size Relay Series
- Input Voltage = 12 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 2 A
- Non Polarized, Monostable Coil Magnetic System

[View all Features](#)

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

TE Internal Number: 1-1617038-8

Active

[Add to My Part List](#)

[Request Sample](#)[Find Similar Products](#)[Buy Product](#)

- None Available

- [RELAY](#) (PDF, English)

- None Available

- None Available

- None Available

- None Available

- Product Line Information

- Tooling

List all Documents

- Termination Type = PC Pins

- Input Voltage (VDC) = 12
- Contact Current Rating (A) = 2
- Coil Polarity Protection Diode = Without
- Transistor Driver = Without
- Coil Resistance ( $\Omega$ ) = 160
- MOSFET Driver = Without
- Coil Power Measurement = Milliwatts
- Coil Power, Nominal (mW) = 900
- Actuating System = DC
- Shock = 100G's, 6ms
- Vibration = 30G's, 10 to 3000Hz

- Series = HMB Half-Size Relay

- Mounting Options = PC Board
- Enclosure Type = Hermetically Sealed
- Approved Standards = M39016 Qualified, M Level

- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Coil Magnetic System = Non Polarized, Monostable
- Coil Suppression Diode = Without

- Government/Industry Qualification = Yes
- Government/Industry Part Number = M39016/22-016M
- RoHS/ELV Compliance = Not ELV/RoHS compliant
- Lead Free Solder Processes = Not suitable for lead free processing

- Temperature Range (°C) = -65 - +125

- Brand = CII

BOOKMARK

## Careers

[Site Map](#)[Manage Your Account](#)

Enter your email address

Follow us on: