

SR-7601 Product Details

Share
Print



SR-7601
(1617084 -3)

TE Internal Number: 1617084
- 3

Active

Military/Aerospace High Performance Relays

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- ? SR Half -size Relay Series
- ? Input Voltage = 26.5 VDC
- ? Contact Arrangement = 4 Form C, 4PDT, 4 C/O
- ? Contact - Rated Current = 2 A
- ? Non Polarized, Monostable Coil - Magnetic System

[View all Features](#)

Quick Links

- ? [Check Pricing & Availability](#)
- ? [Search for Tooling](#)
- ? [Product Feature Selector](#)
- ? [Contact Us About This Product](#)

Documentation & Additional Information	
Product Drawings: <ul style="list-style-type: none"> ? None Available Catalog Pages/Data Sheets: <ul style="list-style-type: none"> ? RELAY (PDF, English) Product Specifications: <ul style="list-style-type: none"> ? None Available Application Specifications: <ul style="list-style-type: none"> ? None Available Instruction Sheets: <ul style="list-style-type: none"> ? None Available CAD Files: <ul style="list-style-type: none"> ? None Available 	Additional Information: <ul style="list-style-type: none"> ? Product Line Information Related Products: <ul style="list-style-type: none"> ? Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: <ul style="list-style-type: none"> ? Series = SR Half -size Relay ? Termination Type = Solder Hook Terminals Electrical Characteristics: <ul style="list-style-type: none"> ? Input Voltage (VDC) = 26.5 ? Contact - Rated Current (A) = 2 ? Coil Polarity Protection Diode = Without ? Transistor Driver = Without ? Coil Resistance (?) = 390 ? MOSFET Driver = Without ? Coil Power Measurement = Milliwatts ? Coil - Rated Power (mW) = 1801 ? Actuating System = DC ? Shock = 100G's, 6ms ? Vibration = 15G's, 10 to 2000Hz Contact Features: <ul style="list-style-type: none"> ? Mounting Options = Chassis Mount ? Enclosure Type = Hermetically Sealed 	Configuration Features: <ul style="list-style-type: none"> ? Contact Arrangement = 4 Form C, 4PDT, 4 C/O ? Coil - Magnetic System = Non Polarized, Monostable ? Coil Suppression Diode = Without Industry Standards: <ul style="list-style-type: none"> ? Government/Industry Qualification = Yes ? Government/Industry Part Number = M39016/40 -001 ? RoHS/ELV Compliance = Not ELV/RoHS compliant ? Lead Free Solder Processes = Not suitable for lead free processing ? Approved Standards = M39016 Qualified Conditions for Usage: <ul style="list-style-type: none"> ? Temperature Range (°C) = -65 - +125 Other: <ul style="list-style-type: none"> ? Brand = CII

Corporate Information

[Who We Are](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address

