



+ RELAYS, CONTACTORS & SWITCHES

TO-5/.100 GRID



✓ Active

TE CONNECTIVITY (TE)
J1MSW-6XP = M39016/10-019P

CII | 1MS TO-5 Relay

J1MSW-6XP
TE Internal Number: 1617120-8
Mil-Spec: M39016/10-019P

Not EU RoHS Compliant
Not EU ELV Compliant

Contact Arrangement 1 Form C, SPDT, 1 C/O

Input Voltage (VDC) 6

Coil Suppression Diode Without

MOSFET Driver Without

Transistor Driver Without

↓ 3D PDF

DOCUMENTATION

CAD Files

3D PDF

PDF

3D

Customer View Model

2D_DXF.ZIP

English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

RELAY

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

- MOSFET Driver Without
- Product Type Relay
- Relay Type Military/Aerospace High Performance
- Enclosure Type Hermetically Sealed

Configuration Features

- Transistor Driver Without

Electrical Characteristics

- Coil Power Measurement Milliwatts
- Input Voltage (VDC) 6
- Coil Suppression Diode Without
- Coil Voltage (VDC) 6
- Coil Resistance (Ω) 255
- Coil Power Rating (DC) (mW) 141
- Coil Polarity Protection Diode Without
- Shock 75G's, 6ms
- Actuating System DC
- Vibration 30G's, 10 – 3000Hz
- Coil Magnetic System Non-Polarized, Monostable

Contact Features

- Contact Arrangement 1 Form C, SPDT, 1 C/O
- Contact Current Rating (A) 1
- Contact Current Class Low Level – 1 A

Termination Features

- Termination Type Long Leads

Mechanical Attachment

- Mounting Type Printed Circuit Board

Usage Conditions

- Operating Temperature Range (°C) -65 – 125

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
